

PT09A-12-10S(444)

PT09A-12-10S(444) Information

Heisener.com	PT09A-12-10S(444) Amphenol Industrial Operations Connectors, Interconnects Circular Connectors CONN RCPT 10POS PNL MNT SKT - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PT09A-12-10S(444) Specifications

Manufacturer Part NumberPT09A-12-10S(444)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation.Shell Material, Finish-Contact Finish-Contact Finish-Shell Material, Finish-Contact Finis		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Yoltage - Rated600VACCurrent Rating7.5A	Manufacturer Part Number	PT09A-12-10S(444)
InitialCircular ConnectorsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation.Shell Material, Finish-Shell Material, Finish-Shell Material, Finish6.Contact Finish-Yoltage - Rated6.00VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation.Ingress Protection-Shell Material, Finish-Contact Finish-Fastening Type-Shell Material, Finish-Contact Finish-Fastening-Shell Material, Finish-Contact Finish-Fastening-Stell Stell Stel	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientation.Ingress Protection-Shell Material, Finish-Contact Finish-Features-Vitage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Fastening-Yoltage - Rated600VACKurent Rating5.54	Package	-
Number of Positions10Shell Size - Insert12-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert12-10Shell Size, MIL-Mouning TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Connector Type	Receptacle, Female Sockets
Interfact and Shell Size, MILInterfact and Shell Size, MILMounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Number of Positions	10
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	12-10
TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Size, MIL	-
Fastening TypeBayonet LockOrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Mounting Type	Panel Mount, Flange
OrientationN(Normal)Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Termination	Solder Cup
Ingress Protection-Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish-Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Orientation	N (Normal)
Contact Finish-Features-Voltage - Rated600VACCurrent Rating7.5A	Ingress Protection	-
Features-Voltage - Rated600VACCurrent Rating7.5A	Shell Material, Finish	-
Voltage - Rated600VACCurrent Rating7.5A	Contact Finish	-
Current Rating 7.5A	Features	-
-	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PT09A-12-10S(444) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

PT09A-12-10S(444) Payment Methods



PT09A-12-10S(444) Shipping Methods



If you have any question about PT09A-12-10S(444), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com