

PT270220 Information



For Reference Only

Part Number PT270220

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 12A 220V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT270220 Specifications

Manufacturer Part NumberPT270220ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPT, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.4mACoil Voltage220VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)165 VDCTurn Off Voltage (Min)22 VDCOperate Time15msRelease Time10msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPT, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.4mACoil Voltage220VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)165 VDCTurn Off Voltage (Min)22 VDCOperate Time15msRelease Time10msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketable	Manufacturer Part Number	PT270220
Package - Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 3.4mA Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 3.4mA Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Category	Relays
SeriesPT, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.4mACoil Voltage220VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)165 VDCTurn Off Voltage (Min)22 VDCOperate Time15msRelease Time10msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketable		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current3.4mACoil Voltage220VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)165 VDCTurn Off Voltage (Min)22 VDCOperate Time15msRelease Time10msFeaturesMechanical Indicator, Test ButtonMounting TypeSocketable	Package	-
Coil Type Non Latching Coil Current 3.4mA Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Series	PT, SCHRACK
Coil Current Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type 3.4mA 220VDC	Relay Type	General Purpose
Coil Voltage 220VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type DPDT (2 Form C) 12A 400VAC - Max 165 VDC 10Turn Off Voltage (Min) 22 VDC 15ms Release Time Socketable	Coil Current	3.4mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Coil Voltage	220VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 165 VDC Turn Off Voltage (Min) 22 VDC Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Contact Rating (Current)	12A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Switching Voltage	400VAC - Max
Operate Time 15ms Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Turn On Voltage (Max)	165 VDC
Release Time 10ms Features Mechanical Indicator, Test Button Mounting Type Socketable	Turn Off Voltage (Min)	22 VDC
Features Mechanical Indicator, Test Button Mounting Type Socketable	Operate Time	15ms
Mounting Type Socketable	Release Time	10ms
C 71	Features	Mechanical Indicator, Test Button
Termination Style Plug In, Quick Connect - 0.110" (2.8mm)	Mounting Type	Socketable
	Termination Style	Plug In, Quick Connect - 0.110" (2.8mm)
Report errors?		Report errors?

PT270220 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT270220 Payment Methods





















PT270220 Shipping Methods













If you have any question about PT270220, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com