

PT270548 Information



For Reference Only

Part Number PT270548

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 12A 48V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT270548 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package - Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 38.4 VAC
Category Relays Power Relays, Over 2 Amps Package - Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 400VAC - Max
Package - Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 400VAC - Max
Package - Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Series PT, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Coil Type Non Latching Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Coil Current - Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Coil Voltage 48VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Contact Rating (Current) 12A Switching Voltage 400VAC - Max
Switching Voltage 400VAC - Max
Turn On Voltage (Max) 38.4 VAC
Turn Off Voltage (Min) 14.4 VAC
Operate Time -
Release Time -
Features Mechanical Indicator, Test Button
Mounting Type Socketable
Termination Style Plug In, Quick Connect - 0.110" (2.8mm)
Report errors's

PT270548 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT270548 Payment Methods



















PT270548 Shipping Methods













If you have any question about PT270548, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com