

PT52A615B Information



For Reference Only

Part Number PT52A615B

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 6A 115V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT52A615B Specifications

Manufacturer Part NumberPT52A615BManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPTH, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage115VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketable		
Category Relays Power Relays, Over 2 Amps Package - Series PTH, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.8mA Coil Voltage 115VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Manufacturer Part Number	PT52A615B
Package - Series PTH, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.8mA Coil Voltage 115VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series PTH, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.8mA Coil Voltage 115VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Category	Relays
SeriesPTH, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage115VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage115VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-	Package	-
Coil TypeNon LatchingCoil Current8.8mACoil Voltage115VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)92 VACTurn Off Voltage (Min)34.5 VACOperate Time20msRelease Time20msFeatures-	Series	PTH, SCHRACK
Coil Current 8.8mA Coil Voltage 115VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Coil Current	8.8mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Coil Voltage	115VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 92 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 20ms Release Time 20ms Features -	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features -	Switching Voltage	250VAC - Max
Operate Time 20ms Release Time 20ms Features -	Turn On Voltage (Max)	92 VAC
Release Time 20ms Features -	Turn Off Voltage (Min)	34.5 VAC
Features -	Operate Time	20ms
	Release Time	20ms
Mounting Type Socketable	Features	-
	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

PT52A615B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT52A615B Payment Methods





















PT52A615B Shipping Methods













If you have any question about PT52A615B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com