

PT5R-700 Information

Heisener.com

Part Number PT5R-700

Manufacturer API Delevan Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

Description FIXED IND 5UH 7.4A 12 MOHM TH

Package Radial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PT5R-700 Specifications

Manufacturer API Delevan Inc. Category Inductors, Coils, Chokes Fixed Inductors Package Radial Series PTR Type Toroidal Material - Core - Inductance 5μH Tolerance ±15% Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Manufacturer Part Number	PT5R-700
Fixed Inductors	Manufacturer	API Delevan Inc.
Package Radial Series PTR Type Toroidal Material - Core - Inductance 5µH Tolerance ±15% Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings Operating Temperature Frequency - Test 1kHz	Category	Inductors, Coils, Chokes
Series PTR Type Toroidal Material - Core - Inductance 5μH Tolerance ±15% Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz		Fixed Inductors
Type Toroidal Material - Core - Inductance 5μH Tolerance ±15% Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Package	Radial
Material - Core - Inductance 5μH Tolerance ±15% Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Series	PTR
Inductance $5\mu H$ Tolerance $\pm 15\%$ Current Rating $7.4A$ Current - Saturation-ShieldingUnshieldedDC Resistance (DCR) 12 mOhm Max Q @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-Frequency - Test $1kHz$	Туре	Toroidal
Tolerance ±15% Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Material - Core	-
Current Rating 7.4A Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Inductance	5μΗ
Current - Saturation - Shielding Unshielded DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Tolerance	±15%
Shielding DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test Unshielded 12 mOhm Max - INDEPTITE OF TEMPERATURE - INDEPTITE OF TEMPERATURE INDEPTI	Current Rating	7.4A
DC Resistance (DCR) 12 mOhm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Current - Saturation	-
Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	Shielding	Unshielded
Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 1kHz	DC Resistance (DCR)	12 mOhm Max
Ratings - Operating Temperature - Frequency - Test 1kHz	Q @ Freq	-
Operating Temperature - Frequency - Test 1kHz	Frequency - Self Resonant	-
Frequency - Test 1kHz	Ratings	-
	Operating Temperature	-
Features	Frequency - Test	1kHz
readics -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial	Package / Case	Radial
Supplier Device Package -	Supplier Device Package	
Size / Dimension 0.650" Dia x 0.450" W (16.51mm x 11.43mm)	Size / Dimension	0.650" Dia x 0.450" W (16.51mm x 11.43mm)

Height - Seated (Max)	-
	Report errors?

PT5R-700 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PT5R-700 Payment Methods



















PT5R-700 Shipping Methods













If you have any question about PT5R-700, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com