

Heisener.com

### PTG06SE-18-32S(023) Information

Part Number PTG06SE-18-32S(023)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 32POS INLINE SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PTG06SE-18-32S(023) Specifications

Manufacturer Part Number       PTG06SE-18-32S(023)         Manufacturer       Amphenol Industrial Operations         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-26482 Series I, PT         Connector Type       Plug, Female Sockets         Number of Positions       32         Shell Size - Insert       18-32         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Resistant         Shell Material, Finish       Aluminum, Nickel Plated, Electroless         Contact Finish       Gold         Features       Shielded         Voltage - Rated       600VAC         Current Rating       7.5A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 32 Shell Size - Insert 18-32 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated Current Rating 7.5A	Manufacturer Part Number	PTG06SE-18-32S(023)
Package-SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PT  Connector Type Plug, Female Sockets  Number of Positions 32  Shell Size - Insert 18-32  Shell Size, MIL - Characterian Corimp Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features Shielded  Voltage - Rated 600VAC  Current Rating 7.5A	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series I, PTConnector TypePlug, Female SocketsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions32Shell Size - Insert18-32Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Nickel Plated, ElectrolessContact FinishGoldFeaturesShieldedVoltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Shielded  Voltage - Rated  600VAC  Current Rating  18-32	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Features Shielded  Voltage - Rated 600VAC  Current Rating 7.5A	Number of Positions	32
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Resistant  Shell Material, Finish Aluminum, Nickel Plated, Electroless  Contact Finish Gold  Features Shielded  Voltage - Rated 600VAC  Current Rating 7.5A	Shell Size - Insert	18-32
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Resistant  Shell Material, Finish  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Shielded  Voltage - Rated  600VAC  Current Rating  7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Nickel Plated, Electroless Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection  Environment Resistant  Aluminum, Nickel Plated, Electroless  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Total Current Rating  Environment Resistant  Aluminum, Nickel Plated, Electroless  Gold  Food  Total Current Resistant  Total Current Resistant  Aluminum, Nickel Plated, Electroless  Gold  Total Current Resistant  T	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Gold  Features  Shielded  Voltage - Rated  Current Rating  Aluminum, Nickel Plated, Electroless  Gold  Shielded  7.5A	Orientation	N (Normal)
Contact Finish Gold Features Shielded Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded  Voltage - Rated 600VAC  Current Rating 7.5A	Shell Material, Finish	Aluminum, Nickel Plated, Electroless
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

### PTG06SE-18-32S(023) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PTG06SE-18-32S(023) Payment Methods



















# PTG06SE-18-32S(023) Shipping Methods













If you have any question about PTG06SE-18-32S(023), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com