



PTG06SE-22-55S(SR) Information

Heisener.com

Part Number PTG06SE-22-55S(SR)

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 55POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PTG06SE-22-55S(SR) Specifications

Manufacturer Part Number PTG06SE-22-55S(SR) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Current Rating 7.5A	Manufacturer Part Number	PTG06SE-22-55S(SR)
Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Courrent Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Plug, Female Sockets Number of Positions 55 Shell Size - Insert 22-55 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielded, Strain ReliefVoltage - Rated600VACCurrent Rating7.5A	Package	-
Number of Positions55Shell Size - Insert22-55Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ResistantShell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishGoldFeaturesShielded, Strain ReliefVoltage - Rated600VACCurrent Rating7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Number of Positions	55
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Size - Insert	22-55
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Termination	Crimp
Ingress Protection Environment Resistant Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Gold Contact Finish Gold Shielded, Strain Relief 7.5A	Orientation	N (Normal)
Contact Finish Gold Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	Environment Resistant
Features Shielded, Strain Relief Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	Shielded, Strain Relief
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PTG06SE-22-55S(SR) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PTG06SE-22-55S(SR) Payment Methods



















PTG06SE-22-55S(SR) Shipping Methods













If you have any question about PTG06SE-22-55S(SR), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com