

PTK15-Q24-S5-T Information



For Reference Only

Part Number PTK15-Q24-S5-T

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description CONVERTER DC/DC 5V 15W TERMINAL

Package Modul

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PTK15-Q24-S5-T Specifications

Manufacturer Part Number PTK15-Q24-S5-T Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PTK15 Type Isolated Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PTK15 Type Isolated Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Manufacturer Part Number	PTK15-Q24-S5-T	
Package Module Series PTK15 Type Isolated Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Manufacturer	CUI Inc.	
Package Module Series PTK15 Type Isolated Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series PTK15 Type Isolated Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)		DC DC Converters	
Type Isolated Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Package	Module	
Voltage - Input (Min) 10V Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Series	PTK15	
Voltage - Input (Max) 36V Number of Outputs 1 Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Туре	Isolated	
Number of Outputs 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 15W Applications ITE (Commercial) Operating Temperature -20°C ~71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Voltage - Input (Min)	10V	
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 5V	Voltage - Input (Max)	36V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - Current - Output (Max) AR - C	Number of Outputs	1	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - Current - Output (Max	Voltage - Output 1	5V	
Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) 15W 15W 15W 15W 15W 15W 15W 15	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial) Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 15W Commercial) -20°C ~ 71°C Chassis Mount 15W 15W 15W 15W 15W 15W 15W 15	Voltage - Output 4	-	
Applications ITE (Commercial) Operating Temperature $-20^{\circ}\text{C} \sim 71^{\circ}\text{C}$ Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension $3.00^{\circ}\text{L x } 2.25^{\circ}\text{W x } 0.67^{\circ}\text{H } (76.2\text{mm x } 57.2\text{mm x } 17.0\text{mm})$	Current - Output (Max)	3A	
Operating Temperature -20°C ~ 71°C Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Power (Watts)	15W	
Efficiency 85% Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Applications	ITE (Commercial)	
Mounting Type Chassis Mount Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Operating Temperature	-20°C ~ 71°C	
Package / Case Module Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Efficiency	85%	
Size / Dimension 3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	Mounting Type	Chassis Mount	
	Package / Case	Module	
Report errors	Size / Dimension	3.00" L x 2.25" W x 0.67" H (76.2mm x 57.2mm x 17.0mm)	
•			Report errors?

PTK15-Q24-S5-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PTK15-Q24-S5-T Payment Methods





















PTK15-Q24-S5-T Shipping Methods













If you have any question about PTK15-Q24-S5-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com