

PTN0603E4751BST1

PTN0603E4751BST1 Information



Part Number	PTN0603E4751BST1	
Manufacturer	Vishay Thin Film	
Category	Resistors Chip Resistor - Surface Mount	
Description	RES 4.75K OHM 0.1% 0.15W 0603	
Package	0603 (1608 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PTN0603E4751BST1 Specifications

Manufacturer Part Number PTN0603E4751BST1 Manufacturer Vishay Thin Film Category Resistors Chip Resistor - Surface Mount Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series PTN Resistance 4.75 KOhms Tolerance ±0.1% Power (Watts) 0.15W Composition Thin Film Features Anti-Sulfur, Moisture Resistant, Non-Inductive Package / Case 0603 (1608 Metric) Supplier Device Package 0603 (1608 Metric) Number of Terminations 0.202" (0.51 mm) Height - Seated (Max) 0.020" (0.51 mm) Number of Terminations 2 Failure Rate -		
CategoryResistorsCategoryChip Resistor - Surface MountPackage0603 (1608 Metric)PackagePTNResistance4.75 kOhmsTolerance±0.1%Power (Watts)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature6603 (1608 Metric)Supplier Device Package0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.20" (0.51mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	PTN0603E4751BST1
Chip Resistor - Surface MountPackage0603 (1608 Metric)SeriesPTNResistance4.75 kOhmsTolerance±0.1%Power (Watts)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.20" (0.51mm)Number of Terminations2Failure Rate-	Manufacturer	Vishay Thin Film
Package0603 (1608 Metric)SeriesPTNResistance4.75 kOhmsTolerance±0.1%Power (Wats)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductivePoperating Temperature±25ppm/°COperating Temperature0603 (1608 Metric)Supplier Device Package0603 (1608 Metric)Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Category	Resistors
SeriesPTNResistance4.75 kOhmsTolerance±0.1%Power (Watts)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.20" (0.51mm)Number of Terminations2Failure Rate-		Chip Resistor - Surface Mount
Resistance4.75 kOhmsTolerance±0.1%Power (Watts)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperatureo603 (1608 Metric)Supplier Device Package0603 (1608 Metric)Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.200" (0.51mm)Number of Terminations2Failure Rate-	Package	0603 (1608 Metric)
Tolerance±0.1%Power (Watts)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature6003 (1608 Metric)Package / Case0603 (1608 Metric)Supplier Device Package0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.200" (0.51mm)Number of Terminations2Failure Rate-	Series	PTN
Power (Watts)0.15WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.020" (0.51mm)Number of Terminations2Failure Rate-	Resistance	4.75 kOhms
CompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.200" (0.51mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.1\%$
FeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveFeatures±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.20" (0.51mm)Number of Terminations2Failure Rate-	Power (Watts)	0.15W
Temperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.020" (0.51mm)Number of Terminations2Failure Rate-	Composition	Thin Film
Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.064" L x 0.032" W (1.63mm x 0.81mm) Height - Seated (Max) 0.020" (0.51mm) Number of Terminations 2 Failure Rate -	Features	Anti-Sulfur, Moisture Resistant, Non-Inductive
Package / Case0603 (1608 Metric)Supplier Device Package0603Size / Dimension0.064" L x 0.032" W (1.63mm x 0.81mm)Height - Seated (Max)0.020" (0.51mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±25ppm/°C
Supplier Device Package 0603 Size / Dimension 0.064" L x 0.032" W (1.63mm x 0.81mm) Height - Seated (Max) 0.020" (0.51mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.064" L x 0.032" W (1.63mm x 0.81mm) Height - Seated (Max) 0.020" (0.51mm) Number of Terminations 2 Failure Rate -	Package / Case	0603 (1608 Metric)
Height - Seated (Max)0.020" (0.51mm)Number of Terminations2Failure Rate-	Supplier Device Package	0603
Number of Terminations2Failure Rate-	Size / Dimension	0.064" L x 0.032" W (1.63mm x 0.81mm)
Failure Rate -	Height - Seated (Max)	0.020" (0.51mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

PTN0603E4751BST1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

PTN0603E4751BST1 Payment Methods



PTN0603E4751BST1 Shipping Methods



If you have any question about PTN0603E4751BST1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com