

PTN1206E2051BST1

PTN1206E2051BST1 Information



Part Number	PTN1206E2051BST1	
Manufacturer	Vishay Thin Film	
Category	Resistors Chip Resistor - Surface Mount	
Description	RES SMD 2.05K OHM 0.1% 0.4W 1206	
Package	1206 (3216 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PTN1206E2051BST1 Specifications

Manufacturer Part NumberPTN1206E2051BST1ManufacturerVishay Thin FilmCategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)SeriesPTNResistance2.05 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Supplier Lexicae0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2		
CategoryResistorsCategoryChip Resistor - Surface MountPackage1206 (3216 Metric)PackagePTNResistance2.05 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)2	Manufacturer Part Number	PTN1206E2051BST1
Chip Resistor - Surface MountPackage1206 (3216 Metric)SeriesPTNResistance2.05 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Manufacturer	Vishay Thin Film
Package1206 (3216 Metric)SeriesPTNResistance2.05 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature1206 (3216 Metric)Package / Case1206Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)2	Category	Resistors
SeriesPTNResistance2.05 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2		Chip Resistor - Surface Mount
Resistance2.05 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Package	1206 (3216 Metric)
Tolerance±0.1%Power (Wats)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Series	PTN
Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Resistance	2.05 kOhms
CompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Tolerance	$\pm 0.1\%$
FeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Power (Watts)	0.4W
Temperature Coefficient $\pm 25 pm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 155^{\circ}C$ Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Composition	Thin Film
Operating Temperature -55°C ~ 155°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.033" (0.84mm) Number of Terminations 2	Features	Anti-Sulfur, Moisture Resistant, Non-Inductive
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Temperature Coefficient	±25ppm/°C
Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.033" (0.84mm) Number of Terminations 2	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.033" (0.84mm) Number of Terminations 2	Package / Case	1206 (3216 Metric)
Height - Seated (Max)0.033" (0.84mm)Number of Terminations2	Supplier Device Package	1206
Number of Terminations 2	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
	Height - Seated (Max)	0.033" (0.84mm)
	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report error:		Report errors?

PTN1206E2051BST1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

PTN1206E2051BST1 Payment Methods



PTN1206E2051BST1 Shipping Methods



If you have any question about PTN1206E2051BST1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com