

PTN1206E4121BST1

PTN1206E4121BST1 Information



Part Number	PTN1206E4121BST1	
Manufacturer	Vishay Thin Film	
Category	Resistors Chip Resistor - Surface Mount	
Description	RES SMD 4.12K OHM 0.1% 0.4W 1206	
Package	1206 (3216 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



PTN1206E4121BST1 Specifications

Manufacturer Part Number PTN1206E4121BST1 Manufacturer Vishay Thin Film Category Resistors Chip Resistor - Surface Mount Chip Resistor - Surface Mount Package 1206 (3216 Metric) Series PTN Resistance 4.12 kOhms Tolerance ±0.1% Power (Watts) 0.4W Composition Thin Film Features Anti-Sulfur, Moisture Resistant, Non-Inductive Operating Temperature ±25ppm/°C Package / Case 1206 (3216 Metric) Supplier Device Package 0.033" (0.84mm) Number of Terminations 2 Failure Rate -		
CategoryResistorsCategoryChip Resistor - Surface MountPackage1206 (3216 Metric)PackagePTNResistance4.12 kOhmsTolerance9.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	PTN1206E4121BST1
Chip Resistor - Surface MountPackage1206 (3216 Metric)SeriesPTNResistance4.12 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)0.033° (0.84mm)Number of Terminations2Failure Rate-	Manufacturer	Vishay Thin Film
Package1206 (3216 Metric)SeriesPTNResistance4.12 kOhmsTolerance±0.1%Power (Wats)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductivePoperating Temperature±25ppm/°COperating Temperature1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)2Number of Terminations2Failure Rate-	Category	Resistors
Series PTN Resistance 4.12 kOhms Tolerance ±0.1% Power (Watts) 0.4W Composition Thin Film Features Anti-Sulfur, Moisture Resistant, Non-Inductive Temperature Coefficient ±25pm/°C Operating Temperature -55°C ~ 155°C Package / Case 1206 (3216 Metric) Supplier Device Package 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.033" (0.84mm) Number of Terminations 2 Failure Rate -		Chip Resistor - Surface Mount
Resistance4.12 kOhmsTolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Package	1206 (3216 Metric)
Tolerance±0.1%Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Series	PTN
Power (Watts)0.4WCompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Resistance	4.12 kOhms
CompositionThin FilmFeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Tolerance	$\pm 0.1\%$
FeaturesAnti-Sulfur, Moisture Resistant, Non-InductiveTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Power (Watts)	0.4W
Temperature Coefficient±25ppm/°COperating Temperature-55°C ~ 155°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Composition	Thin Film
Operating Temperature -55°C ~ 155°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.033" (0.84mm) Number of Terminations 2 Failure Rate -	Features	Anti-Sulfur, Moisture Resistant, Non-Inductive
Package / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Temperature Coefficient	±25ppm/°C
Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.033" (0.84mm) Number of Terminations 2 Failure Rate -	Package / Case	1206 (3216 Metric)
Height - Seated (Max)0.033" (0.84mm)Number of Terminations2Failure Rate-	Supplier Device Package	1206
Number of Terminations2Failure Rate-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Failure Rate -	Height - Seated (Max)	0.033" (0.84mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

PTN1206E4121BST1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

စာ MoneyGram <u>Alipay</u> VISA

DISCOVER

PTN1206E4121BST1 Payment Methods



PTN1206E4121BST1 Shipping Methods



If you have any question about PTN1206E4121BST1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com