

**PTP902-030K-502B2 Information**


For Reference Only

**Part Number** [PTP902-030K-502B2](#)  
**Manufacturer** Bourns Inc.  
**Category** Potentiometers, Variable Resistors  
[Rotary Potentiometers, Rheostats](#)  
**Description** POT 5K OHM 1/20W CARBON LINEAR  
**Package** -  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)



[Request a Quote](#)

**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**PTP902-030K-502B2 Specifications**

Manufacturer Part Number	<a href="#">PTP902-030K-502B2</a>
Manufacturer	Bourns Inc.
Category	Potentiometers, Variable Resistors <a href="#">Rotary Potentiometers, Rheostats</a>
Package	-
Series	Pro Audio PTP90
Taper	Linear
Resistance (Ohms)	5k
Tolerance	±20%
Number of Gangs	2
Built in Switch	None
Power (Watts)	0.05W, 1/20W
Temperature Coefficient	-
Number of Turns	1
Rotation	310°
Adjustment Type	Side Adjustment
Resistive Material	Carbon
Termination Style	PC Pins, Board Locks
Actuator Type	Knurled and Slotted
Actuator Length	1.181" (30.00mm)
Actuator Diameter	0.236" (6.00mm)
Bushing Thread	M7 x 0.75
Mounting Type	Panel Mount

[Report errors?](#)

## PTP902-030K-502B2 Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## PTP902-030K-502B2 Payment Methods



## PTP902-030K-502B2 Shipping Methods



If you have any question about PTP902-030K-502B2, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)