

# PTR016V0155-BK

#### PTR016V0155-BK Information

Heisener.com	Part Number Manufacturer Category Description Package	PTR016V0155-BK Eaton Circuit Protection PTC Resettable Fuses PTC RESETTABLE RADIAL 16V 1.55A Radial, Disc For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## PTR016V0155-BK Specifications

Manufacturer Part NumberPTR016V0155-BKManufacturerEatonCategoryCircuit ProtectionPTC Resettable FusesPackageRadial, DiscSeriesPolyTron?, PTR016VTypePolymericVoltage - Max16VCurrent - Max40ACurrent - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)40 MonsResistance - Post Trip (R1) (Max)100 mohmsResistance - SS°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiseSize / Dimension-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Spacing-	•	
CategoryCircuit ProtectionPackageRadial, DiscPackageRadial, DiscSeriesPolyTron?, PTR016VTypePolymericVoltage - Max16VCurrent - Max40ACurrent - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Manufacturer Part Number	PTR016V0155-BK
PackagePTC Resettable FusesPackageRadial, DiscSeriesPolyTron?, PTR016VTypePolymericVoltage - Max16VCurrent - Max40ACurrent - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Sor Cryp)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Manufacturer	Eaton
PackageRadial, DiscSeriesPolyTron?, PTR016VTypePolymericVoltage - Max16VCurrent - Max40ACurrent - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeStanderPackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Category	Circuit Protection
SeriesPolyTon?, PTR016VTypePolymericVoltage - Max16VCurrent - Max40ACurrent - Hold (lh) (Max)1.55ACurrent - Trip (lt)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-		PTC Resettable Fuses
TypePolymericVoltage - Max16VCurrent - Max40ACurrent - Max1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Package	Radial, Disc
Voltage - Max16VCurrent - Max40ACurrent - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Series	PolyTron?, PTR016V
Current - Max40ACurrent - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Туре	Polymeric
Current - Hold (Ih) (Max)1.55ACurrent - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Voltage - Max	16V
Current - Trip (It)3.1ATime to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Current - Max	40A
Time to Trip600msResistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Current - Hold (Ih) (Max)	1.55A
Resistance - Initial (Ri) (Min)43 mOhmsResistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting Type-Package / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Current - Trip (It)	3.1A
Resistance - Post Trip (R1) (Max)100 mOhmsResistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Time to Trip	600ms
Resistance - 25°C (Typ)-Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Resistance - Initial (Ri) (Min)	43 mOhms
Operating Temperature-40°C ~ 85°CRatings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Resistance - Post Trip (R1) (Max)	100 mOhms
Ratings-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Resistance - 25°C (Typ)	-
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Operating Temperature	-40°C ~ 85°C
Package / CaseRadial, DiscSize / Dimension-Height - Seated (Max)-Thickness (Max)-	Ratings	-
Size / Dimension-Height - Seated (Max)-Thickness (Max)-	Mounting Type	Through Hole
Height - Seated (Max)-Thickness (Max)-	Package / Case	Radial, Disc
Thickness (Max) -	Size / Dimension	-
	Height - Seated (Max)	-
Lead Spacing -	Thickness (Max)	-
	Lead Spacing	-
Report en		Report errors?

#### PTR016V0155-BK Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

#### PTR016V0155-BK Payment Methods



### PTR016V0155-BK Shipping Methods



If you have any question about PTR016V0155-BK, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com