

PTS530 JK055 SMTR LFS

PTS530 JK055 SMTR LFS Information



For Reference Only

Part Number PTS530 JK055 SMTR LFS

Manufacturer C&K

Category Switches
Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PTS530 JK055 SMTR LFS Specifications

Manufacturer Part Number PTS530 JK055 SMTR LFS Manufacturer C&K Category Switches Tactile Switches Package - Series PTS530 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage .0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features - Report errors?		
Category Switches Package - Series PTS530 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -	Manufacturer Part Number	PTS530 JK055 SMTR LFS
Package - Series PTS530 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Type, Color Illumination Voltage (Nominal) - COperating Force 260gf Ingress Protection - Series	Manufacturer	C&K
Package - Series PTS530 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -	Category	Switches
Series PTS530 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeFlushMounting TypeSurface MountActuator Height off PCB, Vertical0.55mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline4.50mm x 4.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features-	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -	Series	PTS530
Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Flush Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 0.55mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features - Features - Features - Features - Surface Mount Surface Mount Flush Surface Mount Actuator Orientation O.55mm Actuator Actuator One Actuator One Actuator Angle - Surface Mount Surface Mount Actuator Mount Top Actuated - Actuator Orientation Top Actuated - Actuator Orientation Top Actuated - Surface Mount Actuator Mount Top Actuated - - 260gf Flush Surface Mount - Surface	Switch Function	Off-Mom
Mounting TypeSurface MountActuator Height off PCB, Vertical0.55mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline4.50mm x 4.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features-	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Common Actuated Top Actuated Termination Style Outline J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features O.55mm O.55mm O.55mm O.55mm Features	Actuator Type	Flush
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features - - - - - - - - - - - - -	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -	Actuator Height off PCB, Vertical	0.55mm
Termination Style J Lead Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features -	Actuator Length, Right Angle	-
Outline 4.50mm x 4.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Features Features Features Features Indicated A.50mm x 4.50mm A.5	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-Features-	Termination Style	J Lead
Illumination Type, Color	Outline	4.50mm x 4.50mm
Illumination Voltage (Nominal) Operating Force 260gf Ingress Protection - Features -	Illumination	Non-Illuminated
Operating Force 260gf Ingress Protection - Features -	Illumination Type, Color	-
Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	260gf
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

PTS530 JK055 SMTR LFS Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PTS530 JK055 SMTR LFS Payment Methods



















PTS530 JK055 SMTR LFS Shipping Methods













If you have any question about PTS530 JK055 SMTR LFS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com