

PTY03A-8-2S Information

Heisener.com

Part Number PTY03A-8-2S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 2POS WALL MNT SKT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PTY03A-8-2S Specifications

Manufacturer Part NumberPTY03A-8-2SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series I, PTConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert8-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Tin PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features Voltage - Rated 600VAC Current Rating 7.5A	Manufacturer Part Number	PTY03A-8-2S
Circular Connectors Package - Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 8-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating 7.5A	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 8-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Category	Connectors, Interconnects
Series MIL-DTL-26482 Series I, PT Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 8-2 Shell Size, MIL		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 8-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Package	-
Number of Positions Shell Size - Insert 8-2 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features Voltage - Rated Current Rating 7.5A	Series	MIL-DTL-26482 Series I, PT
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated Current Rating 7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated Courrent Rating 7.5A	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Tin PlatedContact FinishGoldFeatures-Voltage - Rated600VACCurrent Rating7.5A	Shell Size - Insert	8-2
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated Current Rating Bayonet Lock N (Normal) - 600VAC 7.5A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Tin Plated Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum, Tin Plated Gold	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 600VAC Current Rating 7.5A	Ingress Protection	-
Features - Voltage - Rated 600VAC Current Rating 7.5A	Shell Material, Finish	Aluminum, Tin Plated
Voltage - Rated 600VAC Current Rating 7.5A	Contact Finish	Gold
Current Rating 7.5A	Features	-
	Voltage - Rated	600VAC
Report errors?	Current Rating	7.5A
		Report errors?

PTY03A-8-2S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PTY03A-8-2S Payment Methods





















PTY03A-8-2S Shipping Methods













If you have any question about PTY03A-8-2S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com