

PV-3A10-T Information

Heisener.com

Part Number PV-3A10-T Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 3A 1KVDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PV-3A10-T Specifications

Manufacturer Part Number PV-3A10-T Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series PV Fuse Type Cartridge Current Rating 3A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPVFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Manufacturer Part Number	PV-3A10-T
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series PV Fuse Type Cartridge Current Rating 3A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Clatrinal, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cartridge C	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesPVFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Category	Circuit Protection
Series PV Fuse Type Cartridge Current Rating 3A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 3A A A A A B A C C CIO CO CO CO CO CO CO CO	Series	PV
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - 1000V (1kV) - CCC, CSA, UC - COC, CSA, UC - CCC, CSA, UC - CCC, CSA, UC - CUC, CSA	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1000V (1kV) 1000V (Current Rating	3A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Solar (Photovoltaic) - Bolt Mount - CCC, CSA, UL -40°C ~ 90°C Breaking Capacity @ Rated Voltage Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) -40°C ~ 90°C S	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Solar (Photovoltaic) - CCC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - COC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) -40°C ~ 90°C Solar (Phot	Voltage Rating - DC	1000V (1kV)
Features - Class - CCC, CSA, UL Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Response Time	-
Class - CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Applications	Solar (Photovoltaic)
Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Features	-
Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Class	-
Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Approvals	CCC, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Operating Temperature	-40°C ~ 90°C
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.406" Dia x 2.319" L (10.30mm x 58.90mm)
		Report errors?

PV-3A10-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PV-3A10-T Payment Methods



















PV-3A10-T Shipping Methods













If you have any question about PV-3A10-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com