

PV-8A10-T Information

Heisener.com

Part Number PV-8A10-T
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 8A 1KVDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PV-8A10-T Specifications

Manufacturer Part NumberPV-8A10-TManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPVFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPVFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Manufacturer Part Number	PV-8A10-T
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series PV Fuse Type Cartridge Current Rating 8A Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses PV Cartridge Cartridge Cartridge Cartridge SA Cartridge SA Cartridge SA Cartridge Cartridge SA Cartridge Cartridge SA SA Cartridge S	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesPVFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Category	Circuit Protection
SeriesPVFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating8AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response Time-ApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCCC, CSA, ULOperating Temperature-40°C ~ 90°CBreaking Capacity @ Rated Voltage50kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 8A 1000V (1kV) - CCC, CSA, UL - COC, CSA,	Series	PV
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - 1000V (1kV) - CCC, CSA, UC - COC, CSA, UC - CCC, CSA, UC - COC, CSA, UC - CUC, CSA	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1000V (1kV) 100	Current Rating	8A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Solar (Photovoltaic) - Bolt Mount CCC, CSA, UL -40°C ~ 90°C Breaking Capacity @ Rated Voltage Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL -40°C ~ 90°C Solar (Photovoltaic) - CUC, CSA, UL - CUC, CSA, U	Voltage Rating - AC	-
Applications Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Solar (Photovoltaic) CCC, CSA, UL - CCC, CSA, UL -40°C ~ 90°C Breaking Capacity @ Rated Voltage Bolt Mount Bolt Mount Cylindrical, Blade Terminal (Bolt) 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Voltage Rating - DC	1000V (1kV)
Features - Class - CCC, CSA, UL Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Response Time	-
Class - CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Applications	Solar (Photovoltaic)
Approvals CCC, CSA, UL Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Features	-
Operating Temperature -40°C ~ 90°C Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Class	-
Breaking Capacity @ Rated Voltage 50kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Approvals	CCC, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Operating Temperature	-40°C ~ 90°C
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 0.406" Dia x 2.319" L (10.30mm x 58.90mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.406" Dia x 2.319" L (10.30mm x 58.90mm)
		Report errors?

PV-8A10-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PV-8A10-T Payment Methods



















PV-8A10-T Shipping Methods













If you have any question about PV-8A10-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com