

PV76L14-5PW Information

Heisener.com

Part Number PV76L14-5PW Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 5POS STRAIGHT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PV76L14-5PW Specifications

Manufacturer Part Number PV76L14-5PW Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-26482 Series II, PV Connector Type Plug, Male Pins Number of Positions 5 Shell Size - Insert 14-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26482 Series II, PVConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Manufacturer Part Number	PV76L14-5PW
Package-SeriesMIL-DTL-26482 Series II, PVConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-26482 Series II, PVConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Category	Connectors, Interconnects
SeriesMIL-DTL-26482 Series II, PVConnector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Package	-
Number of Positions5Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Series	MIL-DTL-26482 Series II, PV
Shell Size - Insert14-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Connector Type	Plug, Male Pins
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress Protection-Shell Material, FinishAluminum Alloy, Nickel Plated, ElectrolessContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Shell Size - Insert	14-5
Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating -	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation W Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating -	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum Alloy, Nickel Plated, Electroless Contact Finish Gold Features - Voltage - Rated - Current Rating -	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Aluminum Alloy, Nickel Plated, Electroless Gold	Orientation	W
Contact Finish Gold Features - Voltage - Rated - Current Rating -	Ingress Protection	-
Features - Voltage - Rated - Current Rating -	Shell Material, Finish	Aluminum Alloy, Nickel Plated, Electroless
Voltage - Rated - Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

PV76L14-5PW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PV76L14-5PW Payment Methods



















PV76L14-5PW Shipping Methods













If you have any question about PV76L14-5PW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com