

PVM-25 Information

Heisener.com

Part Number PVM-25
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 25A 600VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PVM-25 Specifications

Manufacturer Part Number PVM-25 Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series PVM? Fuse Type Cartridge Current Rating 25A Voltage Rating - AC - Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPVM?Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer Part Number	PVM-25
Beaking Capacity @ Rated Voltage Fleetrical, Specialty Fuses Cartridge, Non-Standard PVM? Fuse Type Cartridge Current Rating 25A Voltage Rating - AC - Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension PVM? Features Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Eaton
Package Cartridge, Non-Standard Series PVM? Fuse Type Cartridge Current Rating 25A Voltage Rating - AC - Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesPVM?Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals Cysa, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 25A 600V Cov Cov Fast Fast Solar (Photovoltaic) Foats Solar (Photovoltaic) Foats Foats Solar (Photovoltaic) Foats Foats Solar (Photovoltaic) Foats Foats Solar (Photovoltaic) Foats Foats Foats Foats Cov Cov Cov Cov Cov Cov Cov Co	Series	PVM?
Voltage Rating - AC Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cartridge, Non-Standard Size / Dimension - CONV 600V Fast CONV CONV Fast Contridge, Non-Standard O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600	Current Rating	25A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Solar (Photovoltaic) - CSA, UL	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Solar (Photovoltaic) - CARTRIDATE OF THE PHOTO	Voltage Rating - DC	600V
Features - Class - CSA, UL Approvals CSA, UL Operating Temperature - Fracking Capacity @ Rated Voltage SOkA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Fast
Class - Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

PVM-25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PVM-25 Payment Methods



















PVM-25 Shipping Methods













If you have any question about PVM-25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com