

Heisener.com

## PX2AS2XX150PSBDX

#### PX2AS2XX150PSBDX Information

Part Number PX2AS2XX150PSBDX

Manufacturer Honeywell Sensing and Productivity Solutions

Sensors, Transducers Category

Pressure Sensors, Transducers

**Description** HEAVY DUTY PRESSURE TRANSDUCER

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# PX2AS2XX150PSBDX Specifications

Manufacturer Part Number       PX2AS2XX150PSBDX         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       Cylinder         Series       PX2         Pressure Type       Sealed Gauge         Operating Pressure       150 PSI (1034.21 kPa)         Output Type       Analog Voltage         Output       0.25 V ~ 10.25 V         Accuracy       ±0.25%         Voltage - Supply       13 V ~ 30 V         Port Size       Male - 7/16" (11.11mm) UNF         Port Style       Threaded         Features       Temperature Compensated         Termination Style       Connector         Maximum Pressure       450 PSI (3102.64 kPa)         Operating Temperature       -40°C ~ 125°C         Package / Case       Cylinder         Supplier Device Package       -         Report errors?		
CategorySensors, TransducersPackageCylinderSeriesPX2Pressure TypeSealed GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply13 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Manufacturer Part Number	PX2AS2XX150PSBDX
Package Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output O	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeriesPX2Pressure TypeSealed GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply13 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesPX2Pressure TypeSealed GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply13 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply13 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Package	Cylinder
Operating Pressure Output Type Analog Voltage Output 0.25 V ~ 10.25 V Accuracy ±0.25% Voltage - Supply Port Size Male - 7/16" (11.11mm) UNF Port Style Features Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package  -  150 PSI (1034.21 kPa) Analog Voltage 40.25 V To.25	Series	PX2
Output TypeAnalog VoltageOutput0.25 V ~ 10.25 VAccuracy±0.25%Voltage - Supply13 V ~ 30 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Sealed Gauge
Output $0.25 \text{ V} \sim 10.25 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $13 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 7/16" (11.11mm) \text{ UNF}$ Port Style $Threaded$ Features $Temperature Compensated$ Termination Style $Connector$ Maximum Pressure	Operating Pressure	150 PSI (1034.21 kPa)
Accuracy ±0.25%  Voltage - Supply 13 V ~ 30 V  Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Temperature Compensated  Termination Style Connector  Maximum Pressure 450 PSI (3102.64 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  Port Size  Male - 7/16" (11.11mm) UNF  Port Style  Threaded  Features  Temperature Compensated  Termination Style  Connector  Maximum Pressure  450 PSI (3102.64 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Cylinder  Supplier Device Package  -	Output	0.25 V ~ 10.25 V
Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Temperature Compensated  Termination Style Connector  Maximum Pressure 450 PSI (3102.64 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder  Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	13 V ~ 30 V
Features Temperature Compensated  Termination Style Connector  Maximum Pressure 450 PSI (3102.64 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder  Supplier Device Package -	Port Size	Male - 7/16" (11.11mm) UNF
Termination Style Connector  Maximum Pressure 450 PSI (3102.64 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder  Supplier Device Package -	Port Style	Threaded
Maximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C  Package / Case Cylinder  Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	450 PSI (3102.64 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

#### PX2AS2XX150PSBDX Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### PX2AS2XX150PSBDX Payment Methods



















# PX2AS2XX150PSBDX Shipping Methods













If you have any question about PX2AS2XX150PSBDX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com