

Heisener.com

PX2BF1XX025BSCHX

PX2BF1XX025BSCHX Information

Part Number PX2BF1XX025BSCHX

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description HEAVY DUTY PRESSURE TRANSDUCER

Package Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PX2BF1XX025BSCHX Specifications

Manufacturer Part Number Manufacturer Honeywell Sensing and Productivity Solutions Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Features Temperature Compensated Features Temperature Compensated Connector Maximum Pressure Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package Pressure Sensors, Transducers Pressure Sensors, Transducers Pressure Sensors, Transducers Package / Case Sensors, Transducers Pressure Sensors, Transducers Package / Case Sensors / Tansducers Package		
Category Sensors, Transducers Pressure Sensors, Transducers Package Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Features Tempination Style Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package Sensors, Transducers PX2 Pressure Sensors, Transducers PX2 Package / Case Cylinder Suplier Device Package	Manufacturer Part Number	PX2BF1XX025BSCHX
Package Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure Operating Pressure Analog Current Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeriesPX2Pressure TypeSealed GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeFemale - 7/16" (11.11mm) UNF SchraderPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure1000.76 PSI (6900 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Category	Sensors, Transducers
SeriesPX2Pressure TypeSealed GaugeOperating Pressure362.59 PSI (2500 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeFemale - 7/16" (11.11mm) UNF SchraderPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure1000.76 PSI (6900 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 362.59 PSI (2500 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package	Package	Cylinder
Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 362.59 PSI (2500 kPa) Analog Current 4 mA ~ 20 mA TemA TemA TemA TemBerature (11.11mm) UNF Schrader Threaded Temperature Compensated Connector Accuracy 1000.76 PSI (6900 kPa) -40°C ~ 125°C	Series	PX2
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeFemale - 7/16" (11.11mm) UNF SchraderPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure1000.76 PSI (6900 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Pressure Type	Sealed Gauge
Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Operating Pressure	362.59 PSI (2500 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size Female - $7/16$ " (11.11mm) UNF Schrader Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure $1000.76 \text{ PSI } (6900 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case Cylinder Supplier Device Package	Output Type	Analog Current
Voltage - Supply 8 V ~ 30 V Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package -	Output	4 mA ~ 20 mA
Port Size Female - 7/16" (11.11mm) UNF Schrader Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Temperature Compensated Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Size	Female - 7/16" (11.11mm) UNF Schrader
Termination Style Connector Maximum Pressure 1000.76 PSI (6900 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Port Style	Threaded
Maximum Pressure1000.76 PSI (6900 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinderSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder Supplier Device Package -	Maximum Pressure	1000.76 PSI (6900 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder
Report errors?	Supplier Device Package	-
		Report errors?

PX2BF1XX025BSCHX Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PX2BF1XX025BSCHX Payment Methods



















PX2BF1XX025BSCHX Shipping Methods













If you have any question about PX2BF1XX025BSCHX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com