

PX2DN1XX100PSCHX

PX2DN1XX100PSCHX Information



For Reference Only

Part Number PX2DN1XX100PSCHX

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description PRESSURE TRANSDUCER 100PSI NPT

Package Cylinder

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PX2DN1XX100PSCHX Specifications

Manufacturer PX2DN1XX100PSCHX Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder Sunnlier Device Package -		
Category Sensors, Transducers Package Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Manufacturer Part Number	PX2DN1XX100PSCHX
Pressure Sensors, Transducers Cylinder Series PX2 Pressure Type Sealed Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinderSeriesPX2Pressure TypeSealed GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure450 PSI (3102.64 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder	Category	Sensors, Transducers
Pressure Type Sealed Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Package / Case		Pressure Sensors, Transducers
Pressure Type Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Saled Gauge Analog Current Analog Current (6.85mm) NPT Connector Maximum Pressure Connector Cylinder	Package	Cylinder
Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Series	PX2
Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Pressure Type	Sealed Gauge
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.25\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination StyleConnectorMaximum Pressure $450 \text{ PSI } (3102.64 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder	Operating Pressure	100 PSI (689.48 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 1/4" (6.35\text{mm}) \text{ NPT}$ Port Style $Threaded$ Features $Temperature Compensated$ Termination Style $Connector$ Maximum Pressure $Connector$ Connector	Output Type	Analog Current
Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Output	4 mA ~ 20 mA
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style Connector Maximum Pressure 450 PSI (3102.64 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Voltage - Supply	8 V ~ 30 V
Features Temperature Compensated Termination Style Connector Maximum Pressure $450 \text{ PSI } (3102.64 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case Cylinder	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Connector Maximum Pressure $450 \text{ PSI } (3102.64 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case Cylinder	Port Style	Threaded
Maximum Pressure $450 \text{ PSI } (3102.64 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder	Features	Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder	Termination Style	Connector
Package / Case Cylinder	Maximum Pressure	450 PSI (3102.64 kPa)
	Operating Temperature	-40°C ~ 125°C
Supplier Device Package -	Package / Case	Cylinder
supplied be vice I would	Supplier Device Package	-
Report errors?		Report errors?

PX2DN1XX100PSCHX Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PX2DN1XX100PSCHX Payment Methods





















PX2DN1XX100PSCHX Shipping Methods













If you have any question about PX2DN1XX100PSCHX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com