



PXC.M0.8GG.NR Information

Heisener.com

Part Number PXC.M0.8GG.NR

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description RCPT PNL MNT 8SKT R/A PCB

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PXC.M0.8GG.NR Specifications

Manufacturer Part Number PXC.M0.8GG.NR Manufacturer LEMO Category Connectors, Interconnects Package - Series 1P Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert M08 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A		
CategoryConnectors, InterconnectsPackage-Series1PConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationCIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesBackshellVoltage - Rated-Current Rating5A	Manufacturer Part Number	PXC.M0.8GG.NR
Circular Connectors Package - Series IP Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert M08 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated Current Rating 54	Manufacturer	LEMO
Package-Series1PConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationCIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesBackshellVoltage - Rated-Current Rating5A	Category	Connectors, Interconnects
Series1PConnector TypeReceptacle, Female SocketsNumber of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationCIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesBackshellVoltage - Rated-Current Rating5A		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 8 Shell Size - Insert M08 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Package	-
Number of Positions8Shell Size - InsertM08Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationCIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesBackshellVoltage - Rated-Current Rating5A	Series	1P
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Bulkhead; Through Hole, Right Angle Termination Solder Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Number of Positions	8
Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-Pull, Detent LockOrientationCIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeaturesBackshellVoltage - Rated-Current Rating5A	Shell Size - Insert	M08
Termination Solder Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated Current Rating 5A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Mounting Type	Panel Mount, Bulkhead; Through Hole, Right Angle
Orientation C Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Termination	Solder
Ingress Protection Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Orientation	C
Contact Finish Gold Features Backshell Voltage - Rated - Current Rating 5A	Ingress Protection	IP50 - Dust Protected
Features Backshell Voltage - Rated - Current Rating 5A	Shell Material, Finish	Polysulfone (PSU)
Voltage - Rated - Current Rating 5A	Contact Finish	Gold
Current Rating 5A	Features	Backshell
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

PXC.M0.8GG.NR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PXC.M0.8GG.NR Payment Methods





















PXC.M0.8GG.NR Shipping Methods













If you have any question about PXC.M0.8GG.NR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com