



Heisener.com

PXM6011/02P/ST/0405 Information

Part Number PXM6011/02P/ST/0405

Manufacturer Bulgin

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT IN-LINE 2POS PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PXM6011/02P/ST/0405 Specifications

Manufacturer Part Number PXM6011/02P/ST/0405 Manufacturer Bulgin Category Connectors, Interconnects Circular Connectors Package - Series Buccaneer? 6000 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - Report errors?			
Category Connectors, Interconnects Circular Connectors Package - Series Buccaneer? 6000 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated Current Rating - Connectors, Interconnects Circular Connectors - Connectors Succenses - Connector Succenses	Manufacturer Part Number	PXM6011/02P/ST/0405	
Circular Connectors Package - Series Buccaneer? 6000 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Manufacturer	Bulgin	
Package-SeriesBuccaneer? 6000Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Nickel PlatedContact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Category	Connectors, Interconnects	
SeriesBuccaneer? 6000Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Nickel PlatedContact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-		Circular Connectors	
Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Nickel PlatedContact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Package	-	
Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Nickel PlatedContact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Series	Buccaneer? 6000	
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Connector Type	Receptacle, Male Pins	
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated Current Rating - - - - - - - - - - - - -	Number of Positions	2	
Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Nickel PlatedContact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Shell Size - Insert	-	
Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Shell Size, MIL	-	
Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Mounting Type	Free Hanging (In-Line)	
Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Termination	Screw	
Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Nickel Plated Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Fastening Type	Push-Twist	
Shell Material, Finish Contact Finish Nickel Features - Voltage - Rated Current Rating	Orientation	Keyed	
Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Ingress Protection	IP66/68/69K - Dust Tight, Water Resistant, Waterproof	
Features - Voltage - Rated 277VAC/DC Current Rating -	Shell Material, Finish	Brass, Nickel Plated	
Voltage - Rated 277VAC/DC Current Rating -	Contact Finish	Nickel	
Current Rating -	Features	-	
	Voltage - Rated	277VAC/DC	
Report errors?	Current Rating	-	
•		Repo	ort errors?

PXM6011/02P/ST/0405 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PXM6011/02P/ST/0405 Payment Methods



















PXM6011/02P/ST/0405 Shipping Methods













If you have any question about PXM6011/02P/ST/0405, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com