



PXP6010/03S/ST Information

Heisener.com

Part Number PXP6010/03S/ST

Manufacturer Bulgin

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 3POS INLINE SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PXP6010/03S/ST Specifications

Manufacturer Part Number PXP6010/03S/ST Manufacturer Bulgin Category Connectors, Interconnects Package - Series Buccaneer? 6000 Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesBuccaneer? 6000Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Manufacturer Part Number	PXP6010/03S/ST
Package-SeriesBuccaneer? 6000Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Manufacturer	Bulgin
Package - Series Buccaneer? 6000 Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - 277VAC/DC Current Rating	Category	Connectors, Interconnects
SeriesBuccaneer? 6000Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Package	-
Number of Positions3Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Series	Buccaneer? 6000
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features Voltage - Rated 277VAC/DC Current Rating -	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-	Shell Size - Insert	-
Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Shell Size, MIL	-
Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Termination	Screw
Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Fastening Type	Push-Twist
Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Orientation	Keyed
Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating -	Ingress Protection	IP66/68/69K - Dust Tight, Water Resistant, Waterproof
Features - Voltage - Rated 277VAC/DC Current Rating -	Shell Material, Finish	Polycarbonate/Polybutylene Terephthalate (PBT)
Voltage - Rated 277VAC/DC Current Rating -	Contact Finish	Nickel
Current Rating -	Features	-
	Voltage - Rated	277VAC/DC
Report errors?	Current Rating	-
		Report errors?

PXP6010/03S/ST Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PXP6010/03S/ST Payment Methods



















PXP6010/03S/ST Shipping Methods













If you have any question about PXP6010/03S/ST, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com