

Heisener.com

PXP6011/02P/ST/0405

PXP6011/02P/ST/0405 Information

Part Number PXP6011/02P/ST/0405

Manufacturer Bulgin

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT IN-LINE 2POS PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PXP6011/02P/ST/0405 Specifications

Manufacturer Part NumberPXP6011/02P/ST/0405ManufacturerBulginCategoryConnectors, InterconnectsPackage-SeriesBuccaneer? 6000Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating-			
CategoryConnectors, InterconnectsPackage-SeriesBuccaneer? 6000Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DC	Manufacturer Part Number	PXP6011/02P/ST/0405	
Circular Connectors Package - Series Buccaneer? 6000 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features Voltage - Rated Connectors Buccaneer? 6000 Receptacle, Male Pins 2 Receptacle, Male Pins Peceptacle, Male Pins Peceptacle, Male Pins Pecept	Manufacturer	Bulgin	
Package - Series Buccaneer? 6000 Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Steel Hanging (In-Line) Termination Screw Free Hanging (In-Line) Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Category	Connectors, Interconnects	
SeriesBuccaneer? 6000Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DC		Circular Connectors	
Connector Type Receptacle, Male Pins Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features Voltage - Rated 277VAC/DC	Package	-	
Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DC	Series	Buccaneer? 6000	
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features Voltage - Rated 277VAC/DC	Connector Type	Receptacle, Male Pins	
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Number of Positions	2	
Mounting Type Free Hanging (In-Line) Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Shell Size - Insert	-	
Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Shell Size, MIL	-	
Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Mounting Type	Free Hanging (In-Line)	
Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Termination	Screw	
Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Fastening Type	Push-Twist	
Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Orientation	Keyed	
Contact Finish Nickel Features - Voltage - Rated 277VAC/DC	Ingress Protection	IP66/68/69K - Dust Tight, Water Resistant, Waterproof	
Features - Voltage - Rated 277VAC/DC	Shell Material, Finish	Polycarbonate/Polybutylene Terephthalate (PBT)	
Voltage - Rated 277VAC/DC	Contact Finish	Nickel	
	Features	-	
Current Rating -	Voltage - Rated	277VAC/DC	
	Current Rating	-	
Report errors?		F	Report errors?

PXP6011/02P/ST/0405 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PXP6011/02P/ST/0405 Payment Methods



















PXP6011/02P/ST/0405 Shipping Methods













If you have any question about PXP6011/02P/ST/0405, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com