



PXP6012/02S/ST Information



For Reference Only

Part Number PXP6012/02S/ST

Manufacturer Bulgin

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT PNL MNT 2POS SKTS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PXP6012/02S/ST Specifications

| Manufacturer Part Number PXP6012/02S/ST Manufacturer Bulgin Category Connectors, Interconnects Circular Connectors Package - Series Buccaneer? 6000 Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - Report errors? | | |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesBuccaneer? 6000Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating- | Manufacturer Part Number | PXP6012/02S/ST |
| Package-SeriesBuccaneer? 6000Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating- | Manufacturer | Bulgin |
| Package - Series Buccaneer? 6000 Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - 277VAC/DC Current Rating | Category | Connectors, Interconnects |
| SeriesBuccaneer? 6000Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Rear Side NutTerminationScrewFastening TypePush-TwistOrientationKeyedIngress ProtectionIP66/68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolycarbonate/Polybutylene Terephthalate (PBT)Contact FinishNickelFeatures-Voltage - Rated277VAC/DCCurrent Rating- | | Circular Connectors |
| Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Package | - |
| Number of Positions Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features Voltage - Rated 277VAC/DC Current Rating - | Series | Buccaneer? 6000 |
| Shell Size - Insert - Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Rear Side Nut Screw - Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Number of Positions | 2 |
| Mounting Type Panel Mount, Bulkhead - Rear Side Nut Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Shell Size - Insert | - |
| Termination Screw Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Shell Size, MIL | - |
| Fastening Type Push-Twist Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Mounting Type | Panel Mount, Bulkhead - Rear Side Nut |
| Orientation Keyed Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Termination | Screw |
| Ingress Protection IP66/68/69K - Dust Tight, Water Resistant, Waterproof Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Fastening Type | Push-Twist |
| Shell Material, Finish Polycarbonate/Polybutylene Terephthalate (PBT) Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Orientation | Keyed |
| Contact Finish Nickel Features - Voltage - Rated 277VAC/DC Current Rating - | Ingress Protection | IP66/68/69K - Dust Tight, Water Resistant, Waterproof |
| Features - Voltage - Rated 277VAC/DC Current Rating - | Shell Material, Finish | Polycarbonate/Polybutylene Terephthalate (PBT) |
| Voltage - Rated 277VAC/DC Current Rating - | Contact Finish | Nickel |
| Current Rating - | Features | - |
| | Voltage - Rated | 277VAC/DC |
| Report errors? | Current Rating | - |
| | | Report errors? |

PXP6012/02S/ST Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PXP6012/02S/ST Payment Methods



















PXP6012/02S/ST Shipping Methods













If you have any question about PXP6012/02S/ST, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com