



PYB15-Q24-D15-U Information



For Reference Only

Part Number PYB15-Q24-D15-U

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERTER +/-15V 15W UFRM

Package Modul

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PYB15-Q24-D15-U Specifications

Manufacturer Part Number PYB15-Q24-D15-U Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PYB15-U Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PYB15-U Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Manufacturer Part Number	PYB15-Q24-D15-U
Package Module Series PYB15-U Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Manufacturer	CUI Inc.
Package Module Series PYB15-U Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series PYB15-U Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Package	Module
Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Series	PYB15-U
Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Туре	Isolated
Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Voltage - Input (Min)	9V
Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Voltage - Input (Max)	36V
Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Number of Outputs	2
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - 500mA, 500mA - 500mA 500mA - 600mA 500mA 500mA 600mA	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension - Output (Max) - Size / Dimension 500mA, 500mA - Company - Chassis Mount - Chassis Moun	Voltage - Output 2	-15V
Current - Output (Max) 500mA, 500mA Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Voltage - Output 3	-
Power (Watts) 15W Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Voltage - Output 4	-
Applications - Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Current - Output (Max)	500mA, 500mA
Operating Temperature -40°C ~ 85°C Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Power (Watts)	15W
Efficiency 88% Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Applications	-
Mounting Type Chassis Mount Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Module Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Efficiency	88%
Size / Dimension 2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)	Mounting Type	Chassis Mount
	Package / Case	Module
Report errors?	Size / Dimension	2.16" L x 2.06" W x 0.75" H (54.9mm x 52.3mm x 19.1mm)
		Report errors?

PYB15-Q24-D15-U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PYB15-Q24-D15-U Payment Methods



















PYB15-Q24-D15-U Shipping Methods













If you have any question about PYB15-Q24-D15-U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com