



PYB20-Q24-D15-DIN Information



Part Number PYB20-Q24-D15-DIN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERTER +/-15V 20W DIN

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









PYB20-Q24-D15-DIN Specifications

Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PYB20-DIN Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series PYB20-DIN Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Manufacturer Part Number	PYB20-Q24-D15-DIN	
Package Module Series PYB20-DIN Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Manufacturer	CUI Inc.	
Package Module Series PYB20-DIN Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series PYB20-DIN Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)		DC DC Converters	
Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Package	Module	
Voltage - Input (Min) 9V Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Series	PYB20-DIN	
Voltage - Input (Max) 36V Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Туре	Isolated	
Number of Outputs 2 Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Voltage - Input (Min)	9V	
Voltage - Output 1 15V Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Voltage - Input (Max)	36V	
Voltage - Output 2 -15V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Number of Outputs	2	
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Voltage - Output 1	15V	
Voltage - Output 4 Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Voltage - Output 2	-15V	
Current - Output (Max) 667mA, 667mA Power (Watts) 20W Applications - Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Voltage - Output 3	-	
Power (Watts) Applications Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Voltage - Output 4	-	
Applications	Current - Output (Max)	667mA, 667mA	
Operating Temperature -40°C ~ 85°C Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Power (Watts)	20W	
Efficiency 86% Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Applications	-	
Mounting Type DIN Rail Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Operating Temperature	-40°C ~ 85°C	
Package / Case Module Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Efficiency	86%	
Size / Dimension 2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	Mounting Type	DIN Rail	
	Package / Case	Module	
Report errors?	Size / Dimension	2.99" L x 1.24" W x 0.87" H (76.0mm x 31.5mm x 22.2mm)	
			Report errors?

PYB20-Q24-D15-DIN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

PYB20-Q24-D15-DIN Payment Methods



















PYB20-Q24-D15-DIN Shipping Methods













If you have any question about PYB20-Q24-D15-DIN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com