



# **Q8F3BZZRYG24E** Information



For Reference Only

Part Number Q8F3BZZRYG24E

Manufacturer APEM Inc.

Category Optoelectronics

Panel Indicators, Pilot Lights

**Description** LED PMI FLUSH GRN/RED/YLW

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **Q8F3BZZRYG24E Specifications**

Manufacturer Part Number         Q8F3BZZRYG24E           Manufacturer         APEM Inc.           Category         Optoelectronics           Panel Indicators, Pilot Lights           Package         -           Series         Q Series           Type         LED           Lamp Color         Green, Red, Yellow           Lens Color         -           Lens Transparency         Diffused           Ratings         DC           Voltage         24V Green, 24V Red, 24V Yellow           Current         20mA Green, 20mA Red, 20mA Yellow           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.31" (7.87mm)           Lens Style/Size         Round with Flat Top, 5mm (T-1 3/4)           Millicandela Rating         10mcd Green, 15mcd Red, 6mcd Yellow           Wavelength - Peak         -           Viewing Angle         100°           Termination Style         Wire Leads - 7.87" (200.00mm)           Ingress Protection         IP67           Features         -           Leads - 7.87" (200.00mm)		
CategoryOptoelectronicsPackage-SeriesQ SeriesTypeLEDLamp ColorGreen, Red, YellowLens TransparencyDiffusedRatingsDCVoltage24V Green, 24V Red, 24V YellowCurrent20mA Green, 20mA Red, 20mA YellowPanel Cutout ShapeRoundPanel Cutout Dimensions0.31" (7.87mm)Lens Style/SizeRound with Flat Top, 5mm (T-1 3/4)Millicandela Rating10mcd Green, 15mcd Red, 6mcd YellowWavelength - Peak-Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-	Manufacturer Part Number	Q8F3BZZRYG24E
Package - Series Q Series Type LED Lamp Color Green, Red, Yellow Lens Transparency Diffused Ratings DC Voltage 24V Green, 24V Red, 24V Yellow Current 20mA Green, 20mA Red, 20mA Yellow Panel Cutout Shape Round 0.31" (7.87mm) Lens Style/Size Round with Flat Top, 5mm (T-1 3/4) Millicandela Rating 100° Wavelength - Peak - Viewing Angle 100° Termination Style Wire Leads - 7.87" (200.00mm) Features - IED Series Q Series  UED  Green, 20mA Green, 20mA Red, 20mA Yellow Round With Flat Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow Wavelength - Peak - Viewing Angle 100° Termination Style Wire Leads - 7.87" (200.00mm) Ingress Protection 1P67 Features - LED	Manufacturer	APEM Inc.
Package-SeriesQ SeriesTypeLEDLamp ColorGreen, Red, YellowLens Color-Lens TransparencyDiffusedRatingsDCVoltage24V Green, 24V Red, 24V YellowCurrent20mA Green, 20mA Red, 20mA YellowPanel Cutout ShapeRoundPanel Cutout Dimensions0.31" (7.87mm)Lens Style/SizeRound with Flat Top, 5mm (T-1 3/4)Millicandela Rating10mcd Green, 15mcd Red, 6mcd YellowWavelength - Peak-Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-	Category	Optoelectronics
SeriesQ SeriesTypeLEDLamp ColorGreen, Red, YellowLens Color-Lens TransparencyDiffusedRatingsDCVoltage24V Green, 24V Red, 24V YellowCurrent20mA Green, 20mA Red, 20mA YellowPanel Cutout ShapeRoundPanel Cutout Dimensions0.31" (7.87mm)Lens Style/SizeRound with Flat Top, 5mm (T-1 3/4)Millicandela Rating10mcd Green, 15mcd Red, 6mcd YellowWavelength - Peak-Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-		Panel Indicators, Pilot Lights
Type LED  Lamp Color Green, Red, Yellow  Lens Color -  Lens Transparency Diffused  Ratings DC  Voltage 24V Green, 24V Red, 24V Yellow  Current 20mA Green, 20mA Red, 20mA Yellow  Panel Cutout Shape Round  Panel Cutout Dimensions 0.31" (7.87mm)  Lens Style/Size Round with Flat Top, 5mm (T-1 3/4)  Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow  Wavelength - Peak  Viewing Angle 100°  Termination Style Wire Leads - 7.87" (200.00mm)  Ingress Protection IP67  Features -	Package	-
Lamp Color Lens Color Lens Transparency Diffused Ratings DC Voltage 24V Green, 24V Red, 24V Yellow Current 20mA Green, 20mA Red, 20mA Yellow Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Flat Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow Wavelength - Peak Viewing Angle 100° Termination Style Mire Leads - 7.87" (200.00mm) Ingress Protection Features	Series	Q Series
Lens Color-Lens TransparencyDiffusedRatingsDCVoltage24V Green, 24V Red, 24V YellowCurrent20mA Green, 20mA Red, 20mA YellowPanel Cutout ShapeRoundPanel Cutout Dimensions0.31" (7.87mm)Lens Style/SizeRound with Flat Top, 5mm (T-1 3/4)Millicandela Rating10mcd Green, 15mcd Red, 6mcd YellowWavelength - Peak-Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-	Туре	LED
Lens TransparencyDiffusedRatingsDCVoltage24V Green, 24V Red, 24V YellowCurrent20mA Green, 20mA Red, 20mA YellowPanel Cutout ShapeRoundPanel Cutout Dimensions0.31" (7.87mm)Lens Style/SizeRound with Flat Top, 5mm (T-1 3/4)Millicandela Rating10mcd Green, 15mcd Red, 6mcd YellowWavelength - Peak-Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-	Lamp Color	Green, Red, Yellow
Ratings DC Voltage 24V Green, 24V Red, 24V Yellow Current 20mA Green, 20mA Red, 20mA Yellow Panel Cutout Shape Round Panel Cutout Dimensions 0.31" (7.87mm) Lens Style/Size Round with Flat Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow Wavelength - Peak - Viewing Angle 100° Termination Style Wire Leads - 7.87" (200.00mm) Ingress Protection IP67 Features -	Lens Color	-
Voltage 24V Green, 24V Red, 24V Yellow Current 20mA Green, 20mA Red, 20mA Yellow Panel Cutout Shape Round Panel Cutout Dimensions 0.31" (7.87mm) Lens Style/Size Round with Flat Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow Wavelength - Peak - Viewing Angle 100° Termination Style Wire Leads - 7.87" (200.00mm) Ingress Protection IP67 Features -	Lens Transparency	Diffused
Current 20mA Green, 20mA Red, 20mA Yellow Panel Cutout Shape Round Panel Cutout Dimensions 0.31" (7.87mm) Lens Style/Size Round with Flat Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow Wavelength - Peak - Viewing Angle 100° Termination Style Wire Leads - 7.87" (200.00mm) Ingress Protection IP67 Features -	Ratings	DC
Panel Cutout Shape Round Panel Cutout Dimensions 0.31" (7.87mm) Lens Style/Size Round with Flat Top, 5mm (T-1 3/4) Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow Wavelength - Peak Viewing Angle 100° Termination Style Wire Leads - 7.87" (200.00mm) Ingress Protection IP67 Features -	Voltage	24V Green, 24V Red, 24V Yellow
Panel Cutout Dimensions  0.31" (7.87mm)  Lens Style/Size  Round with Flat Top, 5mm (T-1 3/4)  Millicandela Rating  10mcd Green, 15mcd Red, 6mcd Yellow  Wavelength - Peak  - Viewing Angle  100°  Termination Style  Wire Leads - 7.87" (200.00mm)  Ingress Protection  IP67  Features  -	Current	20mA Green, 20mA Red, 20mA Yellow
Lens Style/Size Round with Flat Top, 5mm (T-1 3/4)  Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow  Wavelength - Peak -  Viewing Angle 100°  Termination Style Wire Leads - 7.87" (200.00mm)  Ingress Protection IP67  Features -	Panel Cutout Shape	Round
Millicandela Rating 10mcd Green, 15mcd Red, 6mcd Yellow  Wavelength - Peak -  Viewing Angle 100°  Termination Style Wire Leads - 7.87" (200.00mm)  Ingress Protection IP67  Features -	Panel Cutout Dimensions	0.31" (7.87mm)
Wavelength - Peak-Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-	Lens Style/Size	Round with Flat Top, 5mm (T-1 3/4)
Viewing Angle100°Termination StyleWire Leads - 7.87" (200.00mm)Ingress ProtectionIP67Features-	Millicandela Rating	10mcd Green, 15mcd Red, 6mcd Yellow
Termination Style Wire Leads - 7.87" (200.00mm) Ingress Protection IP67 Features -	Wavelength - Peak	-
Ingress Protection IP67 Features -	Viewing Angle	100°
Features -	Termination Style	Wire Leads - 7.87" (200.00mm)
	Ingress Protection	IP67
Report errors?	Features	-
		Report errors?

### **Q8F3BZZRYG24E** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **Q8F3BZZRYG24E Payment Methods**





















## **Q8F3BZZRYG24E Shipping Methods**













If you have any question about Q8F3BZZRYG24E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com