



QBLP679-RGB5 Information

Heisener.com

Part Number QBLP679-RGB5

Manufacturer QT Brightek (QTB)

Category Optoelectronics

LED Indication - Discrete

Description LED RED 6PLCC 5050 SMD

Package 6-SMD, J-Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OBLP679-RGB5	Specifications
ODLFU/9-KGD5	Specifications

Manufacturer Part Number QBLP679-RGB5 Manufacturer QT Brightek (QTB) Category Optoelectronics LED Indication - Discrete Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Clear Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Supplier Device Package 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm		
Category Optoelectronics LED Indication - Discrete Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Clear Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Manufacturer Part Number	QBLP679-RGB5
Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Clear Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Manufacturer	QT Brightek (QTB)
Package 6-SMD, J-Lead Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Lens Transparency Clear Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Category	Optoelectronics
Series - Color Red, Green, Blue (RGB) Configuration Independent Lens Color - Clear Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm		LED Indication - Discrete
ColorRed, Green, Blue (RGB)ConfigurationIndependentLens Color-Lens TransparencyClearMillicandela Rating700mcd Red, 1650mcd Green, 300mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2V Red, 3.2V Green, 3.2V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant625nm Red, 525nm Green, 471nm BlueWavelength - Peak-Features-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension5.00mm L x 5.00mm WHeight (Max)1.80mm	Package	6-SMD, J-Lead
Configuration Independent Lens Color Lens Transparency Clear Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Series	-
Lens Color-Lens TransparencyClearMillicandela Rating700mcd Red, 1650mcd Green, 300mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2V Red, 3.2V Green, 3.2V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant625nm Red, 525nm Green, 471nm BlueWavelength - Peak-Features-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension5.00mm L x 5.00mm WHeight (Max)1.80mm	Color	Red, Green, Blue (RGB)
Lens TransparencyClearMillicandela Rating700mcd Red, 1650mcd Green, 300mcd BlueLens Style/SizeRound with Flat TopVoltage - Forward (Vf) (Typ)2V Red, 3.2V Green, 3.2V BlueCurrent - Test20mA Red, 20mA Green, 20mA BlueViewing Angle120°Mounting TypeSurface MountWavelength - Dominant625nm Red, 525nm Green, 471nm BlueWavelength - Peak-Features-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension5.00mm L x 5.00mm WHeight (Max)1.80mm	Configuration	Independent
Millicandela Rating 700mcd Red, 1650mcd Green, 300mcd Blue Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Lens Color	-
Lens Style/Size Round with Flat Top Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) 2V Red, 3.2V Green, 3.2V Blue Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount 625nm Red, 525nm Green, 471nm Blue Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue	Millicandela Rating	700mcd Red, 1650mcd Green, 300mcd Blue
Current - Test 20mA Red, 20mA Green, 20mA Blue Viewing Angle 120° Mounting Type Surface Mount 625nm Red, 525nm Green, 471nm Blue Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Lens Style/Size	Round with Flat Top
Viewing Angle120°Mounting TypeSurface MountWavelength - Dominant625nm Red, 525nm Green, 471nm BlueWavelength - Peak-Features-Package / Case6-SMD, J-LeadSupplier Device Package6-PLCCSize / Dimension5.00mm L x 5.00mm WHeight (Max)1.80mm	Voltage - Forward (Vf) (Typ)	2V Red, 3.2V Green, 3.2V Blue
Mounting Type Surface Mount Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Current - Test	20mA Red, 20mA Green, 20mA Blue
Wavelength - Dominant 625nm Red, 525nm Green, 471nm Blue Wavelength - Peak - Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Viewing Angle	120°
Wavelength - Peak Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Mounting Type	Surface Mount
Features - Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Wavelength - Dominant	625nm Red, 525nm Green, 471nm Blue
Package / Case 6-SMD, J-Lead Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Wavelength - Peak	-
Supplier Device Package 6-PLCC Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Features	-
Size / Dimension 5.00mm L x 5.00mm W Height (Max) 1.80mm	Package / Case	6-SMD, J-Lead
Height (Max) 1.80mm	Supplier Device Package	6-PLCC
	Size / Dimension	5.00mm L x 5.00mm W
Report errors?	Height (Max)	1.80mm
		Report errors?

QBLP679-RGB5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

QBLP679-RGB5 Payment Methods



















QBLP679-RGB5 Shipping Methods













If you have any question about QBLP679-RGB5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com