

QXK2G684KTPTZH

QXK2G684KTPTZH Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

QXK2G684KTPTZH Specifications

ManufacturerNichiconCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesQXK-ZHCapacitance0.68µFTolerance±10%Voltage Rating - DC200VVoltage Rating - DC400VDielectric MaterialPolyester, MetallizedCopariting Temperature-Voltage Refing - DC40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)Applicationsi.gencey, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-		
Category Category Category Capacitors Film Capacitors Film Capacitors Package Radial Series QXK-ZH Capacitance 0.68µF Tolerance ±10% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polyester, Metallized Series - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.024" L x 0.374" W (26.00mm x 9.50mm) Height - Seated (Max) 0.764" (19.40mm) PC Pins Seator Lead Spacing 0.886" (22.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression Features -	Manufacturer Part Number	QXK2G684KTPTZH
Fin CapacitorsPackageRadialSeriesQXK-ZHCapacitance0.68µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)PC Pins0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Manufacturer	Nichicon
PackageRadialSeriesQXK-ZHCapacitance0.68µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)Per Image Age0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Category	Capacitors
Series QXK-ZH Capacitance 0.68µF Tolerance ±10% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.024" L x 0.374" W (26.00mm x 9.50mm) Height - Seated (Max) 0.764" (19.40mm) Permination PC Pins Lead Spacing 0.886" (22.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression Features -		Film Capacitors
Capacitance0.68µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Package	Radial
Tolerance±10%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)Applications-Features-	Series	QXK-ZH
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)PC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Capacitance	0.68µF
Voltage Rating - DC400VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)Termination0.886" (22.50mm)Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Tolerance	$\pm 10\%$
Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Voltage Rating - AC	200V
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Voltage Rating - DC	400V
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Dielectric Material	Polyester, Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Operating Temperature	$-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Size / Dimension1.024" L x 0.374" W (26.00mm x 9.50mm)Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.764" (19.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Size / Dimension	1.024" L x 0.374" W (26.00mm x 9.50mm)
Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Height - Seated (Max)	0.764" (19.40mm)
ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.886" (22.50mm)
	Applications	High Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression
Report errors?	Features	-
		Report errors?

QXK2G684KTPTZH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

QXK2G684KTPTZH Payment Methods





If you have any question about QXK2G684KTPTZH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com