

QXK2J473KTPTZH

QXK2J473KTPTZH Information



Part Number	QXK2J473KTPTZH	
Manufacturer	Nichicon	
Category	Capacitors Film Capacitors	
Description	CAP FILM 0.047UF 10% 630VDC RAD	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
us		
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



QXK2J473KTPTZH Specifications

Manufacturer Part NumberQXK2J473KTPTZHManufacturerNichiconCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesQXK-ZHCapacitance0.047µFTolerance±10%Voltage Rating - AC250VVoltage Rating - AC630VDielectric MaterialPolyester, MetallizedDoperating Temperature40°C ~ 105°CMounting TypeNationPackage / CaseRadialSize / Dimension0.807°L x 0.244″ W (20.50mm x 6.20mm)FirminationDefinisLead Spacing0.689° (1.50mm)Lead Spacing0.689° (1.50mm)Firenaresing Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFightresing Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression <th></th> <th></th>		
CategoryCapacitorsPackageRadialSeriesQXK-ZHCapacitance0.047µFCapacitance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, MetallizedPoerating Temperature-Auford Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Feither Seated (Max)0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Manufacturer Part Number	QXK2J473KTPTZH
Film CapacitorsPackageRadialSeriesQXK-ZHCapacitance0.047μFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)Lead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Manufacturer	Nichicon
PackageRadialSeriesQXK-ZHCapacitance0.047µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, MetallizedDielectric Material-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492° (12.50mm x 6.20mm)Height - Seated (Max)0.492° (12.50mm)Lead Spacing0.689° (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Category	Capacitors
Series QXK-ZH Capacitance 0.047µF Tolerance ±10% Voltage Rating - AC 250V Voltage Rating - DC 630V Dielectric Material Polyester, Metallized Dielectric Material - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.492" (12.50mm) x 6.20mm) x 6.20mm) Height - Seated (Max) 0.492" (12.50mm) Lead Spacing 0.689" (17.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression Features -		Film Capacitors
Capacitance0.047µFTolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, MetallizedDielectric Material-Coperating Temperature-40°C ~ 105°CMounting TypeRatialPackage / CaseRatialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)FerminationPC PinsApplications0.689" (17.50mm)Applicationsi.e.Features-	Package	Radial
Tolerance±10%Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.402° (12.50mm x 6.20mm)Height - Seated (Max)O492° (12.50mm)TerminationPC PinsLead Spacing0.689° (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Series	QXK-ZH
Voltage Rating - AC250VVoltage Rating - DC630VDielectric MaterialPolyester, MetallizedDielectric Material-GSR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)PerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Capacitance	0.047µF
Voltage Rating - DC630VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Tolerance	$\pm 10\%$
Dielectric MaterialPolyester, MetallizedDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Voltage Rating - AC	250V
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Voltage Rating - DC	630V
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Dielectric Material	Polyester, Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Operating Temperature	-40°C ~ 105°C
Size / Dimension0.807" L x 0.244" W (20.50mm x 6.20mm)Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.492" (12.50mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Size / Dimension	0.807" L x 0.244" W (20.50mm x 6.20mm)
Lead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; EMI, RFI SuppressionFeatures-	Height - Seated (Max)	0.492" (12.50mm)
Applications High Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression Features -	Termination	PC Pins
Features -	Lead Spacing	0.689" (17.50mm)
	Applications	High Frequency, Switching; High Pulse, DV/DT; EMI, RFI Suppression
	Features	-
Report error		Report errors?

QXK2J473KTPTZH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

QXK2J473KTPTZH Payment Methods





If you have any question about QXK2J473KTPTZH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com