



R10-E1P6-115V Information



For Reference Only

Part Number R10-E1P6-115V

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 6PDT 3A 115V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









R10-E1P6-115V Specifications

Manufacturer Part Number R10-E1P6-115V Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form 6PDT (6 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form 6PDT (6 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	R10-E1P6-115V
Package-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115 VACContact Form6PDT (6 Form C)Contact Rating (Current)3ASwitching Voltage120 VAC, 30 VDC - MaxTurn On Voltage (Max)86 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form 6PDT (6 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115 VACContact Form6PDT (6 Form C)Contact Rating (Current)3ASwitching Voltage120 VAC, 30 VDC - MaxTurn On Voltage (Max)86 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact Form6PDT (6 Form C)Contact Rating (Current)3ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)86 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage115VACContact Form6PDT (6 Form C)Contact Rating (Current)3ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)86 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Series	R10
Coil Current Coil Voltage 115VAC Contact Form 6PDT (6 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features - Mounting Type Socketable Termination Style - Plug In	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form 6PDT (6 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Hounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 6PDT (6 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Coil Current	-
Contact Rating (Current) Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Coil Voltage	115VAC
Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Contact Form	6PDT (6 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Socketable Termination Style 86 VAC 86 VAC - 86 VAC - 86 VAC - 86 VAC - Pug In	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Socketable Termination Style Plug In	Switching Voltage	120VAC, 30VDC - Max
Operate Time Release Time	Turn On Voltage (Max)	86 VAC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

R10-E1P6-115V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

R10-E1P6-115V Payment Methods



















R10-E1P6-115V Shipping Methods













If you have any question about R10-E1P6-115V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com