

### R10-E1X2-24V Information



For Reference Only

Part Number R10-E1X2-24V

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **R10-E1X2-24V Specifications**

Manufacturer Part Number     R10-E1X2-24V       Manufacturer     TE Connectivity Potter & Brumfield Relays       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     R10       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     -       Coil Voltage     24VAC       Contact Form     DPDT (2 Form C)       Contact Rating (Current)     5A       Switching Voltage     120VAC, 30VDC - Max       Turn On Voltage (Max)     18 VAC       Turn Off Voltage (Min)     -       Operate Time     -       Release Time     -       Features     -       Mounting Type     Socketable       Termination Style     Plug In    Report errors?		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         R10           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         120VAC, 30VDC - Max           Turn On Voltage (Max)         18 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer Part Number	R10-E1X2-24V
Package-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         R10           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         24VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         120VAC, 30VDC - Max           Turn On Voltage (Max)         18 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage24V ACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120V AC, 30V DC - MaxTurn On Voltage (Max)18 V ACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Series	R10
Coil Current Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Hounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  5A  Switching Voltage  120VAC, 30VDC - Max  Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  Operate Time  Release Time  -  Release Time  Features  -  Mounting Type  Socketable  Termination Style	Coil Current	-
Contact Rating (Current)  Switching Voltage  120VAC, 30VDC - Max  Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  - Operate Time  - Release Time  - Features  - Mounting Type  Socketable  Termination Style  5A  120VAC, 30VDC - Max  18 VAC  1-  1-  1-  1-  1-  1-  1-  1-  1-  1	Coil Voltage	24VAC
Switching Voltage 120VAC, 30VDC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  -  Retures  Mounting Type  Socketable  Termination Style  18 VAC  1	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	120VAC, 30VDC - Max
Operate Time Release Time	Turn On Voltage (Max)	18 VAC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### R10-E1X2-24V Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# R10-E1X2-24V Payment Methods

































If you have any question about R10-E1X2-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com