



R10-E1X2-V2.5K Information



For Reference Only

Part Number R10-E1X2-V2.5K

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









R10-E1X2-V2.5K Specifications

Manufacturer Part Number R10-E1X2-V2.5K Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current 19.2mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current 19.2mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	R10-E1X2-V2.5K
Package-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current 19.2mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current19.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Series	R10
Coil Current Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time Release Time - Features Mounting Type Socketable Termination Style 19.2mA 48VDC 48VDC 48VDC 5A 5A 120VAC, 30VDC - Max 120VAC, 30VDC - Max 160 170 180 180 180 180 180 180 18	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Hounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time Release Time - Release Time - Mounting Type Socketable Termination Style	Coil Current	19.2mA
Contact Rating (Current) Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style 5A 120VAC, 30VDC - Max 36 VDC - - - - - - - - - - - - -	Coil Voltage	48VDC
Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Socketable Termination Style 36 VDC - Souther Common Style 36 VDC - Souther Common Style Annual Common Style Souther Common Style Annual Common Style Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Socketable Termination Style Plug In	Switching Voltage	120VAC, 30VDC - Max
Operate Time Release Time	Turn On Voltage (Max)	36 VDC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

R10-E1X2-V2.5K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

R10-E1X2-V2.5K Payment Methods





















R10-E1X2-V2.5K Shipping Methods













If you have any question about R10-E1X2-V2.5K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com