

R10-E1Y1-SS220 Information



For Reference Only

Part Number R10-E1Y1-SS220

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE SPDT 3A 3V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









R10-E1Y1-SS220 Specifications

Manufacturer Part Number R10-E1Y1-SS220 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current 13.64mA Coil Voltage 3VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.64mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)3ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	R10-E1Y1-SS220
Package-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.64mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)3ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series R10 Relay Type General Purpose Coil Type Non Latching Coil Current 13.64mA Coil Voltage 3VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.64mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)3ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 13.64mA Coil Voltage 3VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current13.64mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)3ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Series	R10
Coil Current Coil Voltage 3VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time Release Time - Features Mounting Type Socketable Termination Style 13.64mA 15.64mA 15.64mA 16.64m	Relay Type	General Purpose
Coil Voltage 3VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 3A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Hounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time Release Time - Release Time Features - Mounting Type Socketable Termination Style	Coil Current	13.64mA
Contact Rating (Current) Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time - Release Time - Features Mounting Type Socketable Termination Style Java A Source A Source A Source A Plug In	Coil Voltage	3VDC
Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Socketable Termination Style 2.25 VDC	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Socketable Termination Style Plug In	Switching Voltage	120VAC, 30VDC - Max
Operate Time Release Time	Turn On Voltage (Max)	2.25 VDC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

R10-E1Y1-SS220 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

R10-E1Y1-SS220 Payment Methods



















R10-E1Y1-SS220 Shipping Methods













If you have any question about R10-E1Y1-SS220, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com