



#### R10-E2Z4-V15.0K Information



For Reference Only

Part Number R10-E2Z4-V15.0K

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 2A 115V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# R10-E2Z4-V15.0K Specifications

Manufacturer Part Number       R10-E2Z4-V15.0K         Manufacturer       TE Connectivity Potter & Brumfield Relays         Category       Relays         Package       -         Series       R10         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       -         Coil Voltage       115VDC         Contact Form       4PDT (4 Form C)         Contact Rating (Current)       2A         Switching Voltage       120VAC, 30VDC - Max         Turn On Voltage (Max)       86 VDC         Turn Off Voltage (Min)       -         Operate Time       -         Release Time       -         Features       -         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPackage-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)86 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	R10-E2Z4-V15.0K
Package-SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)86 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         R10           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         115 VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         2A           Switching Voltage         120 VAC, 30 VDC - Max           Turn On Voltage (Max)         86 VDC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesR10Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115 VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage120 VAC, 30 VDC - MaxTurn On Voltage (Max)86 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115 VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage120 VAC, 30 VDC - MaxTurn On Voltage (Max)86 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage115VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage120VAC, 30VDC - MaxTurn On Voltage (Max)86 VDCTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Series	R10
Coil Current Coil Voltage 115VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VDC Turn Off Voltage (Min) - Operate Time Release Time - Features Mounting Type Through Hole Termination Style - PC Pin	Relay Type	General Purpose
Coil Voltage 115VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 120VAC, 30VDC - Max Turn On Voltage (Max) 86 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 2A  Switching Voltage 120VAC, 30VDC - Max  Turn On Voltage (Max) 86 VDC  Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole  Termination Style PC Pin	Coil Current	-
Contact Rating (Current)  Switching Voltage  120VAC, 30VDC - Max  Turn On Voltage (Max)  86 VDC  Turn Off Voltage (Min)  - Operate Time  - Release Time  - Features  - Mounting Type  Through Hole  Termination Style  2A  120VAC, 30VDC - Max  86 VDC  -  120	Coil Voltage	115VDC
Switching Voltage 120VAC, 30VDC - Max  Turn On Voltage (Max) 86 VDC  Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  -  Retures  Mounting Type  Through Hole  Termination Style  86 VDC  -  10  10  10  10  10  10  10  10  10	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	120VAC, 30VDC - Max
Operate Time	Turn On Voltage (Max)	86 VDC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Papart arrors?	Termination Style	PC Pin
Report errors:		Report errors?

#### R10-E2Z4-V15.0K Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## R10-E2Z4-V15.0K Payment Methods



















## R10-E2Z4-V15.0K Shipping Methods













If you have any question about R10-E2Z4-V15.0K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com