

R5J560 Information

(A) Heisener.com

For Reference Only

Part Number R5J560
Manufacturer Ohmite
Category Resistors

Through Hole Resistors

Description RES 560 OHM 5W 5% RADIAL

Package Radial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DETECO	C
KOJOOU	Specifications

Manufacturer Part NumberR5J560ManufacturerOhmiteCategoryResistorsPackageRadialSeriesPC-58Resistance560 OhmsTolerance±5%Power (Watts)5WCompositionWirewoundFeaturesFlame Retardant Coating, SafetyTemperature Coefficient±260ppm/°COperating Temperature-Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.625" L x 0.344" W (15.88mm x 8.74mm)Height - Seated (Max)0.516" (13.11mm)Number of Terminations2Failure Rate-	•	
CategoryResistorsPackageRadialSeriesPC-58Resistance560 OhmsTolerance±5%Power (Watts)5WCompositionWirewoundFeaturesFlame Retardant Coating, SafetyTemperature Coefficient±260ppm/°COperating Temperature-Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.625" L x 0.344" W (15.88mm x 8.74mm)Height - Seated (Max)0.516" (13.11mm)Number of Terminations2Failure Rate-	Manufacturer Part Number	R5J560
Package Radial Series PC-58 Resistance 560 Ohms Tolerance ±5% Power (Watts) 5W Composition Wirewound Features Flame Retardant Coating, Safety Temperature Coefficient ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Manufacturer	Ohmite
PackageRadialSeriesPC-58Resistance560 OhmsTolerance±5%Power (Watts)5WCompositionWirewoundFeaturesFlame Retardant Coating, SafetyTemperature Coefficient±260ppm/°COperating Temperature-Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.625" L x 0.344" W (15.88mm x 8.74mm)Height - Seated (Max)0.516" (13.11mm)Number of Terminations2Failure Rate-	Category	Resistors
Series PC-58 Resistance 560 Ohms Tolerance ±5% Power (Watts) 5W Composition Wirewound Features Flame Retardant Coating, Safety Temperature Coefficient ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -		Through Hole Resistors
Resistance560 OhmsTolerance±5%Power (Watts)5WCompositionWirewoundFeaturesFlame Retardant Coating, SafetyTemperature Coefficient±260ppm/°COperating Temperature-Package / CaseRadialSupplier Device PackageRadial LeadSize / Dimension0.625" L x 0.344" W (15.88mm x 8.74mm)Height - Seated (Max)0.516" (13.11mm)Number of Terminations2Failure Rate-	Package	Radial
Tolerance ±5% Power (Watts) 5W Composition Wirewound Features Flame Retardant Coating, Safety Temperature Coefficient ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Series	PC-58
Power (Watts) Composition Wirewound Features Flame Retardant Coating, Safety Temperature Coefficient ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	560 Ohms
Composition Wirewound Features Flame Retardant Coating, Safety Temperature Coefficient ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Tolerance	±5%
Features Flame Retardant Coating, Safety ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Power (Watts)	5W
Temperature Coefficient ±260ppm/°C Operating Temperature - Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Composition	Wirewound
Operating Temperature	Features	Flame Retardant Coating, Safety
Package / Case Radial Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Temperature Coefficient	±260ppm/°C
Supplier Device Package Radial Lead Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-
Size / Dimension 0.625" L x 0.344" W (15.88mm x 8.74mm) Height - Seated (Max) 0.516" (13.11mm) Number of Terminations 2 Failure Rate -	Package / Case	Radial
Height - Seated (Max) Number of Terminations 2 Failure Rate -	Supplier Device Package	Radial Lead
Number of Terminations 2 Failure Rate -	Size / Dimension	0.625" L x 0.344" W (15.88mm x 8.74mm)
Failure Rate -	Height - Seated (Max)	0.516" (13.11mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

R5J560 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

R5J560 Payment Methods



















R5J560 Shipping Methods













If you have any question about R5J560, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com