

R60DI4220AA30J

R60DI4220AA30J Information



Part Number	R60DI4220AA30J
Manufacturer	KEMET
Category	Capacitors Film Capacitors
Description	CAP FILM 2.2UF 5% 63VDC RADIAL
Package	Radial
For the pricing/inventory/lead time, please cont	
	us
Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



R60DI4220AA30J Specifications

ManufacturerKEMETCapacitorsFilm CapacitorsPackageRadialSeriesR60Capacitance2.2µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CVoltage / CaseRadialSize / Dimension0.709° L x 0.236° W (18.00mm x 6.00mm)Height - Seated (Max)0.591° (15.00mm)ApplicationsSols" I SungmanApplicationsGeneral Purpose			
CategoryCapacitorsPackageRadialPackageRadialSeriesR60Capacitance2.2µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709° L x 0.236° W (18.00mm x 6.00mm)Height - Seated (Max)0.591° (15.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	R60DI4220AA30J	
Film CapacitorsPackageRadialSeriesR60Capacitance2.2µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709° L x 0.236° W (18.00mm x 6.00mm)Height - Seated (Max)0.476° (12.10mm)PerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	KEMET	
PackageRadiaSeriesR60Capacitance2.2µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709° L x 0.236° W (18.00mm x 6.00mm)Height - Seated (Max)0.476° (12.10mm)FerminationGeneral PurposeApplicationsGeneral PurposeFeatures-	Category	Capacitors	
SeriesR60Capacitance2.2µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.476" (12.10mm)Height - Seated (Max)0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-		Film Capacitors	
Capacitance2.2µFTolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.476" (12.10mm)Height - Seated (Max)0.591" (15.00mm)CerninationSize / DinsLead Spacing0.591" (15.00mm)Applications-Features-	Package	Radial	
Tolerance±5%Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.476" (12.10mm)Height - Seated (Max)0.476" (15.00mm)CerminationGeneral PurposeApplicationsGeneral PurposeFeatures-	Series	R60	
Voltage Rating - AC40VVoltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	2.2µF	
Voltage Rating - DC63VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	±5%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	40V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	63V	
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized	
Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.709" L x 0.236" W (18.00mm x 6.00mm)Size / Dimension0.476" (12.10mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C	
Size / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.476" (12.10mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.709" L x 0.236" W (18.00mm x 6.00mm)	
Lead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.476" (12.10mm)	
Applications General Purpose Features -	Termination	PC Pins	
Features -	Lead Spacing	0.591" (15.00mm)	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

R60DI4220AA30J Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

R60DI4220AA30J Payment Methods



R60DI4220AA30J Shipping Methods



If you have any question about R60DI4220AA30J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com