

R60GF3470AA6AK

R60GF3470AA6AK Information



Part Number	R60GF3470AA6AK
Manufacturer	KEMET
Category	Capacitors Film Capacitors
Description	CAP FILM 0.47UF 10% 160VDC RAD
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



R60GF3470AA6AK Specifications

ManufacturerKEMETCapacitorsFilm CapacitorsPackageRadialSeriesRofoCapacitance0.47µFTolerance±10%Voltage Rating - DC90VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedDiperating Temperature-Operating Temperature55°C ~ 105°CPackage / CaseRadialSize / Dimension0.532° L x 0.197° W (13.50mm x 5.00mm)Height - Seated (Max)0.394″ (10.00mm)Applications0.394″ (10.00mm)Eventian Series0.394″ (10.00mm)Capacitang Series0.394″ (10.00mm)Series0.394″ (10.00mm)Capacitang Series0.394″ (10.00mm)Capacitang Series0.394″ (10.00mm)Series0.394″ (10.00mm)Series0.394″ (10.00mm)Series0.394″ (10.00mm)Series0.394″ (10.00mm)Series0.394″ (10.00mm)Series0.394″ (10.00mm)Series0.3			
CategoryCapacitorsPackageRadialPackageR60Capacitance0.47µFColerance±10%Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedDoperating Temperature-Operating TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.943" (11.00mm)ParinationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-Features-	Manufacturer Part Number	R60GF3470AA6AK	
Fin CapacitorsPackageRadialSeriesR60Capacitance0.47µFTolerance±10%Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)PerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	KEMET	
PackageRadialSeriesR60Capacitance0.47µFTolerance±10%Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.433" (11.00mm)Height - Seated (Max)0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors	
SeriesR60Capacitance0.47µFTolerance±10%Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-		Film Capacitors	
Capacitance0.47μFTolerance±10%Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.433" (11.00mm) x 5.00mm)Height - Seated (Max)0.433" (11.00mm)PerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Package	Radial	
Tolerance±10%Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Series	R60	
Voltage Rating - AC90VVoltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)FerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.47µF	
Voltage Rating - DC160VDielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)PerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	±10%	
Dielectric MaterialPolyester, Polyethylene Terephthalate (PET) - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	90V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	160V	
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Terephthalate (PET) - Stacked	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C	
Size / Dimension0.532" L x 0.197" W (13.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.532" L x 0.197" W (13.50mm x 5.00mm)	
Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.433" (11.00mm)	
Applications General Purpose Features -	Termination	PC Pins	
Features -	Lead Spacing	0.394" (10.00mm)	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

R60GF3470AA6AK Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

R60GF3470AA6AK Payment Methods





If you have any question about R60GF3470AA6AK, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com