



R60PF21005030K Information



For Reference Only

Part Number R60PF21005030K

ManufacturerKEMETCategoryCapacitorsFilm Capacitors

Description CAP FILM 10000PF 10% 630VDC RAD

Package Radial

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









R60PF21005030K Specifications

ManufacturerKEMETCategoryCapacitorsPackageRadialSeriesR60Capacitance10000pFTolerance±10%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral Purpose	*		
Category Film Capacitors Package Radial Series R60 Capacitance 10000pF Tolerance ±10% Voltage Rating - AC Voltage Rating - DC Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Termination PC Pins Lead Spacing And	Manufacturer Part Number	R60PF21005030K	
Film Capacitors Package Radial Series R60 Capacitance 10000pF Tolerance ±10% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Manufacturer	KEMET	
PackageRadialSeriesR60Capacitance10000pFTolerance±10%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolyester, Polyethylene Terephthalate (PET), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.512" L x 0.157" W (13.00mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors	
R60 Capacitance 10000pF Tolerance ±10% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -		Film Capacitors	
Capacitance 10000pF Tolerance ±10% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Package	Radial	
Tolerance ±10% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Series	R60	
Voltage Rating - AC Voltage Rating - DC 630V Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features	Capacitance	10000pF	
Voltage Rating - DC Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Tolerance	±10%	
Dielectric Material Polyester, Polyethylene Terephthalate (PET), Metallized ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Voltage Rating - AC	220V	
ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) O.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features	Voltage Rating - DC	630V	
Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Dielectric Material	Polyester, Polyethylene Terephthalate (PET), Metallized	
Mounting Type Package / Case Radial Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 7 CP Pins Lead Spacing Applications Package / Case Radial 0.512" L x 0.157" W (13.00mm x 4.00mm) 0.394" (10.00mm) PC Pins General Purpose Features -	ESR (Equivalent Series Resistance)	-	
Package / Case Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Operating Temperature	-55°C ~ 105°C	
Size / Dimension 0.512" L x 0.157" W (13.00mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Mounting Type	Through Hole	
Height - Seated (Max) Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Package / Case	Radial	
Termination PC Pins Lead Spacing 0.394" (10.00mm) Applications General Purpose Features -	Size / Dimension	0.512" L x 0.157" W (13.00mm x 4.00mm)	
Lead Spacing0.394" (10.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.394" (10.00mm)	
Applications General Purpose Features -	Termination	PC Pins	
Features -	Lead Spacing	0.394" (10.00mm)	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

R60PF21005030K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

R60PF21005030K Payment Methods



















R60PF21005030K Shipping Methods













If you have any question about R60PF21005030K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com