

R73PI23304000J

R73PI23304000J Information



umber	R73PI23304000J	
acturer	KEMET	
ry	Capacitors Film Capacitors	
otion	CAP FILM 0.033UF 5% 630VDC RAD	
e	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



R73PI23304000J Specifications

ManufacturerKEMETCategoryCapacitorsFilm CapacitorsPackageRadialSeriesR73Capacitance0.033µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedStress-Operating Temperature-5°C ~ 105°CVoltage / CaseRadialSize / Dimension0.709° L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)Applications0.591" (15.00mm)Applications0.591" (15.00mm)Features-		
CategoryCapacitorsPackageRadialPackageRobinSeriesR73Capacitance0.033µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedDoperating Temperature-Voltage / CaseRadialSize / Dimension0.00° L x 0.33° W (18.00mm x 8.50mm)Height - Seated (Max)0.50° (14.60mm) x 8.50mm)Height - Seated (Max)0.50° (15.00mm)Applications0.50° (15.00mm)Applications0.50° (16.00mm)Applications0.50° (16.00mm)App	Manufacturer Part Number	R73PI23304000J
Film CapacitorsPackageRadialSeriesR73Capacitance0.033µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)Pc Pins0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	KEMET
PackageRadialSeriesR73Capacitance0.033µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709° L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
SeriesR73Capacitance0.033µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.757" (14.60mm) x 8.50mm)Height - Seated (Max)0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-		Film Capacitors
Capacitance0.033µFCoparace±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.575" (14.60mm) x 8.50mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsO.591" (15.00mm)Features-	Series	R73
NoticitiesInterferenceVoltage Rating - AC300VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.033µF
Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-Operating TypeSto° ~ 105°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)Termination0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	300V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	630V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension0.709" L x 0.335" W (18.00mm x 8.50mm)Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.575" (14.60mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.709" L x 0.335" W (18.00mm x 8.50mm)
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.575" (14.60mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

R73PI23304000J Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

R73PI23304000J Payment Methods





If you have any question about R73PI23304000J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com