

R76MN3470SE30J

R76MN3470SE30J Information



mber	R76MN3470SE30J	
cturer	KEMET	
у	Capacitors Film Capacitors	
tion	CAP FILM 0.47UF 5% 400VDC RADIAL	
e	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



R76MN3470SE30J Specifications

SeriesR76Capacitance0.47µFTolerance±5%Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationDC PinsApplicationsMake" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesR76Capacitance0.47 µFTolerance±5%Voltage Rating - AC250 VVoltage Rating - DC400 VDietertic MaterialPolyropylene (PP), MetallizedSeries Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	R76MN3470SE30J
Film CapacitorsPackageRadialSeriesR76Capacitance0.47µFTolerance±5%Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	KEMET
PackageRadialSeriesR76Capacitance0.47μFTolerance±5%Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
SeriesR76Capacitance0.47μFTolerance±5%Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.728" (18.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-		Film Capacitors
Capacitance0.47µFTolerance±5%Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Series	R76
Voltage Rating - AC250VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.47µF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)Termination0.886" (22.50mm)Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	250V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension1.043" L x 0.394" W (26.50mm x 10.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.043" L x 0.394" W (26.50mm x 10.00mm)
Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.728" (18.50mm)
ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.886" (22.50mm)
	Applications	High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

R76MN3470SE30J Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

R76MN3470SE30J Payment Methods





If you have any question about R76MN3470SE30J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com