



RASM10PS Information



For Reference Only

Part Number RASM10PS
Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR JACK 2X5.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RASM10PS Specifications

Manufacturer Part NumberRASM10PSManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.00mm ID (0.079"), 5.50mm OD (0.217")Actual Diameter0.078" (2.00mm ID), 0.252" (6.40mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface MountMounting FeatureBulkhead - Front Side NutTerminationSolderShieldingUnshieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDCCurrent Rating11AReport errors?		
Category Connectors, Interconnects Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated Current Rating Iack Connectors, Interconnects Barrel - Power Connectors - Surkace Solme (2.00mm ID), 0.252" (6.40mm OD) Surface Mount ID), 0.252" (6.40mm OD) Surface Mount Single Switch, Normally Closed Unshielded Surface Mount Solder Shielding Unshielded Insulation Color - Voltage - Rated 24VDC Current Rating	Manufacturer Part Number	RASM10PS
Barrel - Power Connectors Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 1nternal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating	Manufacturer	Switchcraft Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 111A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 111A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating	Package	-
Gender Male Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 11A	Series	-
Industry Recognized Mating Diameter 2.00mm ID (0.079"), 5.50mm OD (0.217") Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Unshielded Features Board Guide Insulation Color Voltage - Rated Current Rating 11A	Connector Type	Jack
Actual Diameter 0.078" (2.00mm ID), 0.252" (6.40mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Mounting Feature Bulkhead - Front Side Nut Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 11A	Gender	Male
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface MountMounting FeatureBulkhead - Front Side NutTerminationSolderShieldingUnshieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDCCurrent Rating11A	Industry Recognized Mating Diameter	2.00mm ID (0.079"), 5.50mm OD (0.217")
Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount Bulkhead - Front Side Nut Termination Solder Unshielded Features Board Guide Insulation Color Voltage - Rated Current Rating Single Switch, Normally Closed Surface Mount Bulkhead - Front Side Nut - Volder Solder Unshielded 24VDC 11A	Actual Diameter	0.078" (2.00mm ID), 0.252" (6.40mm OD)
Mounting TypeSurface MountMounting FeatureBulkhead - Front Side NutTerminationSolderShieldingUnshieldedFeaturesBoard GuideInsulation Color-Voltage - Rated24VDCCurrent Rating11A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature Bulkhead - Front Side Nut Termination Solder Unshielded Features Board Guide Insulation Color Voltage - Rated Current Rating Bulkhead - Front Side Nut 24VDC 11A	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 11A	Mounting Type	Surface Mount
Shielding Unshielded Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 11A	Mounting Feature	Bulkhead - Front Side Nut
Features Board Guide Insulation Color - Voltage - Rated 24VDC Current Rating 11A	Termination	Solder
Insulation Color - Voltage - Rated 24VDC Current Rating 11A	Shielding	Unshielded
Voltage - Rated 24VDC Current Rating 11A	Features	Board Guide
Current Rating 11A	Insulation Color	-
	Voltage - Rated	24VDC
Report errors?	Current Rating	11A
		Report errors?

RASM10PS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RASM10PS Payment Methods



















RASM10PS Shipping Methods













If you have any question about RASM10PS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com