



RASM712P Information

Heisener.com

Part Number RASM712P Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Barrel - Power Connectors

Description CONN PWR JACK 2.5X5.5MM SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RASM712P Specifications

Manufacturer Part NumberRASM712PManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.50mm ID (0.098"), 5.50mm OD (0.217")Actual Diameter0.098" (2.50mm ID), 0.248" (6.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-Current Rating5AReport errors?		
CategoryConnectors, InterconnectsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.50mm ID (0.098"), 5.50mm OD (0.217")Actual Diameter0.098" (2.50mm ID), 0.248" (6.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-Current Rating5A	Manufacturer Part Number	RASM712P
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Fermination Solder Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 5A	Manufacturer	Switchcraft Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Fermination Solder Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 5 5A	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Jack Male Angle June (0.098"), 5.50mm OD (0.217") 0.098" (2.50mm ID), 0.248" (6.30mm OD) 2 Conductors, 3 Contacts Single Switch, Normally Closed Unshielded	Package	-
Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color - Voltage - Rated Current Rating 5A	Series	-
Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Unshielded Features - Insulation Color Voltage - Rated Current Rating 5 A	Connector Type	Jack
Actual Diameter 0.098" (2.50mm ID), 0.248" (6.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Gender	Male
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-Current Rating5A	Industry Recognized Mating Diameter	2.50mm ID (0.098"), 5.50mm OD (0.217")
Internal Switch(s) Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Single Switch, Normally Closed Surface Mount, Right Angle - Unshielded - Solder Unshielded - Solder Shielding Solder Shielding Solder Sol	Actual Diameter	0.098" (2.50mm ID), 0.248" (6.30mm OD)
Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color Voltage - Rated Current Rating Surface Mount, Right Angle - - Surface Mount, Right Angle - Surface Mount, Right Angle - Solder Solder Solder Unshielded - 5A	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-Current Rating5A	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Mounting Type	Surface Mount, Right Angle
Shielding Unshielded Features - Insulation Color - Voltage - Rated - Current Rating 5A	Mounting Feature	-
Features - Insulation Color - Current Rating 5A	Termination	Solder
Insulation Color - Voltage - Rated - Current Rating 5A	Shielding	Unshielded
Voltage - Rated - Current Rating 5A	Features	-
Current Rating 5A	Insulation Color	-
	Voltage - Rated	-
Report errors?	Current Rating	5A
		Report errors?

RASM712P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RASM712P Payment Methods





















RASM712P Shipping Methods













If you have any question about RASM712P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com