



### **RASM732P Information**

Heisener.com

Part Number RASM732P

Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Barrel - Power Connectors

**Description** CONN POWER JACK SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RASM732P Specifications**

Manufacturer Part NumberRASM732PManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter-Actual Diameter0.048" (1.22mm ID), 0.169" (4.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-	•	
Category  Connectors, Interconnects  Barrel - Power Connectors  Package  - Series  - Connector Type  Jack  Gender  Male  Industry Recognized Mating Diameter  - Actual Diameter  0.048" (1.22mm ID), 0.169" (4.30mm OD)  Number of Positions/Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  Mounting Feature  - Termination  Solder  Shielding  Unshielded  Features  - Insulation Color  Connectors, Interconnects  Barrel - Power Connectors  Actual Diameter  - Unshielded  Features  - Insulation Color	Manufacturer Part Number	RASM732P
Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter-Actual Diameter0.048" (1.22mm ID), 0.169" (4.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-	Manufacturer	Switchcraft Inc.
Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter-Actual Diameter0.048" (1.22mm ID), 0.169" (4.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter -  Actual Diameter 0.048" (1.22mm ID), 0.169" (4.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature -  Termination Solder Shielding Unshielded Features -  Insulation Color		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter - Actual Diameter O.048" (1.22mm ID), 0.169" (4.30mm OD) Number of Positions/Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Insulation Color - Insulation Color	Package	-
Gender Male Industry Recognized Mating Diameter - Actual Diameter 0.048" (1.22mm ID), 0.169" (4.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color -	Series	-
Industry Recognized Mating Diameter - 0.048" (1.22mm ID), 0.169" (4.30mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Surface Mount, Right Angle  Mounting Feature - Conductors Solder  Termination Solder  Shielding Unshielded  Features - Insulation Color - Conductors Solder	Connector Type	Jack
Actual Diameter 0.048" (1.22mm ID), 0.169" (4.30mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Surface Mount, Right Angle  Mounting Feature -  Termination Solder  Shielding Unshielded  Features -  Insulation Color -	Gender	Male
Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-	Industry Recognized Mating Diameter	-
Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  - Termination  Solder  Shielding  Unshielded  Features  Insulation Color  Single Switch, Normally Closed  Unshielded  -  Unshielded  -  -  -  -  -  -  -  -  -  -  -  -  -	Actual Diameter	0.048" (1.22mm ID), 0.169" (4.30mm OD)
Mounting Type Surface Mount, Right Angle  Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color -	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-	Internal Switch(s)	Single Switch, Normally Closed
Termination Solder Shielding Unshielded Features - Insulation Color -	Mounting Type	Surface Mount, Right Angle
Shielding Unshielded Features - Insulation Color -	Mounting Feature	-
Features - Insulation Color -	Termination	Solder
Insulation Color -	Shielding	Unshielded
	Features	-
Voltage - Rated -	Insulation Color	-
	Voltage - Rated	-
Current Rating 5A	Current Rating	5A
Report errors?		Report errors?

#### **RASM732P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RASM732P Payment Methods**



















### **RASM732P Shipping Methods**













If you have any question about RASM732P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com