



### **RASM732P Information**

Heisener.com

Part Number RASM732P
Manufacturer Switchcraft Inc.

Category Connectors, Interconnects Barrel - Power Connectors

**Description** CONN POWER JACK SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RASM732P Specifications**

| Manufacturer Part NumberRASM732PManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter-Actual Diameter0.048" (1.22mm ID), 0.169" (4.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-Voltage - Rated-  | •                                   |  |
|---|-------------------------------------|--|
| Category  Connectors, Interconnects  Barrel - Power Connectors  Package  - Series  - Connector Type  Jack  Gender  Male  Industry Recognized Mating Diameter  - Actual Diameter  0.048" (1.22mm ID), 0.169" (4.30mm OD)  Number of Positions/Contacts  Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  Mounting Feature  - Termination  Solder  Shielding  Unshielded  Features  - Insulation Color  Connectors, Interconnects  Barrel - Power Connectors  Actual Diameter  - Unshielded  Features  - Insulation Color | Manufacturer Part Number            | RASM732P                               |
| Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter-Actual Diameter0.048" (1.22mm ID), 0.169" (4.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-  | Manufacturer                        | Switchcraft Inc.                       |
| Package-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter-Actual Diameter0.048" (1.22mm ID), 0.169" (4.30mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-  | Category                            | Connectors, Interconnects              |
| Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter -  Actual Diameter 0.048" (1.22mm ID), 0.169" (4.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature -  Termination Solder Shielding Unshielded Features -  Insulation Color  |                                     | Barrel - Power Connectors              |
| Connector Type Gender Male Industry Recognized Mating Diameter - Actual Diameter O.048" (1.22mm ID), 0.169" (4.30mm OD) Number of Positions/Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features Insulation Color - Insulation Color   | Package                             | -                                      |
| Gender Male Industry Recognized Mating Diameter - Actual Diameter 0.048" (1.22mm ID), 0.169" (4.30mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch, Normally Closed Mounting Type Surface Mount, Right Angle Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color -  | Series                              | -                                      |
| Industry Recognized Mating Diameter - 0.048" (1.22mm ID), 0.169" (4.30mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Surface Mount, Right Angle  Mounting Feature - Conductors Solder  Termination Solder  Shielding Unshielded  Features - Insulation Color - Conductors Solder   | Connector Type                      | Jack                                   |
| Actual Diameter 0.048" (1.22mm ID), 0.169" (4.30mm OD)  Number of Positions/Contacts 2 Conductors, 3 Contacts  Internal Switch(s) Single Switch, Normally Closed  Mounting Type Surface Mount, Right Angle  Mounting Feature -  Termination Solder  Shielding Unshielded  Features -  Insulation Color -  | Gender                              | Male                                   |
| Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single Switch, Normally ClosedMounting TypeSurface Mount, Right AngleMounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-  | Industry Recognized Mating Diameter | -                                      |
| Internal Switch(s)  Single Switch, Normally Closed  Mounting Type  Surface Mount, Right Angle  - Termination  Solder  Shielding  Unshielded  Features  Insulation Color  Single Switch, Normally Closed  Unshielded  -  Unshielded  -  -  -  -  -  -  -  -  -  -  -  -  -   | Actual Diameter                     | 0.048" (1.22mm ID), 0.169" (4.30mm OD) |
| Mounting Type Surface Mount, Right Angle  Mounting Feature - Termination Solder Shielding Unshielded Features - Insulation Color -  | Number of Positions/Contacts        | 2 Conductors, 3 Contacts               |
| Mounting Feature-TerminationSolderShieldingUnshieldedFeatures-Insulation Color-   | Internal Switch(s)                  | Single Switch, Normally Closed         |
| Termination Solder Shielding Unshielded Features - Insulation Color -   | Mounting Type                       | Surface Mount, Right Angle             |
| Shielding Unshielded Features - Insulation Color -  | Mounting Feature                    | -                                      |
| Features - Insulation Color -   | Termination                         | Solder                                 |
| Insulation Color -  | Shielding                           | Unshielded                             |
|   | Features                            | -                                      |
| Voltage - Rated -   | Insulation Color                    | -                                      |
|   | Voltage - Rated                     | -                                      |
| Current Rating 5A   | Current Rating                      | 5A                                     |
| Report errors?  |                                     | Report errors?                         |

#### **RASM732P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RASM732P Payment Methods**



















### **RASM732P Shipping Methods**













If you have any question about RASM732P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com