



## **RBA49DTBD Information**

Heisener.com

Part Number RBA49DTBD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 98POS 0.125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **RBA49DTBD Specifications**

| Manufacturer Part Number         RBA49DTBD           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         49           Number of Positions         98           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Type         Loop Bellows           Color         Green           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C | 12211192122 Specifications  |   |   |
|---|-----------------------------|---|---|
| Category Cand Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 49 Number of Positions 98 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Flange Feature Flange Feature Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature  | Manufacturer Part Number    | RBA49DTBD   |   |
| Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       49         Number of Positions       98         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.125" (3.18mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10µin (0.25µm)         Contact Type       Loop Bellows         Color       Green         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C  | Manufacturer                | Sullins Connector Solutions                               |   |
| Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         49           Number of Positions         98           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Loop Bellows           Color         Green           Flange Feature         Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C  | Category                    | Connectors, Interconnects                                 |   |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   |                             | Card Edge Connectors - Edgeboard Connectors               |   |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Package                     | -   |   |
| GenderFemaleNumber of Positions/Bay/Row49Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Series                      | -   |   |
| Number of Positions/Bay/Row Number of Positions 98 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Loop Bellows Color Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature  | Card Type                   | Non Specified - Dual Edge                                 |   |
| Number of Positions98Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Gender                      | Female  |   |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Number of Positions/Bay/Row | 49  |   |
| Number of Rows       2         Pitch       0.125" (3.18mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Loop Bellows         Color       Green         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C  | Number of Positions         | 98  |   |
| Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Card Thickness              | 0.062" (1.57mm)   |   |
| Features  Mounting Type  Through Hole, Right Angle  Termination  Solder  Contact Material  Phosphor Bronze  Contact Finish  Contact Finish Thickness  10μin (0.25μm)  Contact Type  Loop Bellows  Color  Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C  | Number of Rows              | 2   |   |
| Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Pitch                       | 0.125" (3.18mm)   |   |
| Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Loop Bellows  Color Green  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C  | Features                    | -   |   |
| Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Loop Bellows  Color Green  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C  | Mounting Type               | Through Hole, Right Angle                                 |   |
| Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Loop Bellows  Color Green  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C  | Termination                 | Solder  |   |
| Contact Finish Thickness $10\mu$ in $(0.25\mu m)$<br>Contact Type Loop Bellows<br>Color Green<br>Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125''$ (3.18mm) Dia<br>Operating Temperature $-65^{\circ}$ C $\sim 125^{\circ}$ C  | Contact Material            | Phosphor Bronze   |   |
| Contact Type Loop Bellows  Color Green  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C   | Contact Finish              | Gold  |   |
| Color Green  Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " (3.18mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C  | Contact Finish Thickness    | 10μin (0.25μm)  |   |
| Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C  | Contact Type                | Loop Bellows  |   |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$  | Color                       | Green   |   |
|   | Flange Feature              | Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia |   |
|   | Operating Temperature       | -65°C ~ 125°C   |   |
| Report errors'  |                             | Report errors   | ? |

### **RBA49DTBD Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RBA49DTBD Payment Methods**



















### **RBA49DTBD Shipping Methods**













If you have any question about RBA49DTBD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com