

# RBA50DTAZ-S273

Juote

#### **RBA50DTAZ-S273 Information**

Heisener.com Order service cards terr	Part Number Manufacturer Category Description Package	RBA50DTAZ-S273 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 100POS .125 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **RBA50DTAZ-S273 Specifications**

Manufacturer Part Number RBA50DTAZ-S273   Manufacturer Sullins Connector Solutions   Category Connectors, Interconnects   Card Edge Connectors - Edgeboard Connectors Card Edge Connectors - Edgeboard Connectors   Package -   Series -   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 50   Number of Positions/Bay/Row 50   Number of Positions 0093" (2.36mm)   Number of Rows 2   Pitch 0.125" (3.18mm)   Features -   Mounting Type Through Hole, Right Angle   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Contact Finish Thickness 10µin (0.25µm)   Contact Type Loop Bellows   Contact Type Soler   Color Green   Flange Feature Flush Mont, Side Opening, Unthreaded, 0.125" (3.18mm) Dia			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Card Thickness0093° (2.36mm)Number of Rows2Pitch0.125° (3.18mm)Features-Mouning TypeSolderContact FinishSolderContact FinishGoldContact Finish ThicknessIopalenseContact Finish ThicknessIopalenseContact Finish ThicknessIopalenseContact Finish ThicknessGoldContact Finish ThicknessIopalenseContact Finish ThicknessIopalenseContact Finish ThicknessIopalenseContact Finish ThicknessIopalenseContact Finish ThicknessIopalenseContact Finish ThicknessGoldContact Finish ThicknessIopalenseContact Finish ThicknessIopalense<	Manufacturer Part Number	RBA50DTAZ-S273	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type-Young TypeSolderContact FinishSolderContact Finish Thickness10µin (0.25µm)Contact TypeLog BellowsContact TypeSolderContact TypeSolder <td>Manufacturer</td> <td colspan="2">Sullins Connector Solutions</td>	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type50Contact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.5µm)Contact TypeLoop BellowsColarGreenFlange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessIujui (0.25µm)Contact TypeGreenFlange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65% ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish100Contact FinishGoldContact TypeInongellowsColorGreenFlange FeaturesFinish Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOpenaing Temperature65° ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.093" (2.36mm)Card Thickness2Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Series	-	
Number of Positions/Bay/Row50Number of Positions100Card Thickness0.093" (2.36mm)Card Thickness2Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 100   Card Thickness 0.093" (2.36mm)   Number of Rows 2   Pitch 0.125" (3.18mm)   Features -   Mounting Type -   Mounting Type Solder   Contact Material Posphor Bronze   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Color Green   Flange Feature Fush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness1.0µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Number of Positions/Bay/Row	50	
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJupin (0.25µm)Contact TypeGorenFlange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	100	
Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.093" (2.36mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphoraencalContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Nounting TypeThrough Hole, Right AngleMounting TypeSolderTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness10µin (0.25µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorGreenFlange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)	
Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Green	
	Flange Feature	Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report error	Operating Temperature	-65°C ~ 125°C	
Report error			Report errors?

#### **RBA50DTAZ-S273** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **RBA50DTAZ-S273** Payment Methods



#### **RBA50DTAZ-S273** Shipping Methods



If you have any question about RBA50DTAZ-S273, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com